



Newark®

AN AVNET COMPANY

Harsh Environment Solutions



Start Here

See the newest products and proven solutions for your most challenging applications

Find more online at newark.com

- Connectors
- Solid State Relays
- Thermal Sensors
- Cable Assemblies
- 3-D Printing
- Semiconductors
- Potentiometers
- Ceramic Capacitors
- Inductors
- Industrial Switches

newark.com



Table of Contents

RELAYS, PUSHBUTTONS, INDICATORS & MORE	5
FANS, CONTACTORS, POWER & SWITCHES	6
INDUSTRIAL CONTROLS, TIMERS & ENCLOSURES	7
SENSORS, POTENTIOMETERS & MORE	8
REED SWITCHES, FUSES, POWER & MORE.....	9
INTERCONNECT	10-13
WIRE MANAGEMENT.....	14
TOOLS & PRODUCTION SUPPLIES	15-20
TEST EQUIPMENT	21-30
SOLDERING STATIONS & SUPPLIES.....	31
SOLDERING & ESD SUPPLIES.....	32
PASSIVE COMPONENTS.....	33
ANTENNAS, PASSIVES & SEMIS.....	34

Accounting for the Elements

Whether it's extreme heat, blistering winds, or toxic chemicals – electronics are more susceptible to damage when operating in harsh environments.

Engineers must account for environmental factors – choosing products with the proper qualifications and ratings to protect valuable equipment and personnel. Browse this small sample of Newark's broad portfolio of components, devices, and products tailor-made for harsh and challenging applications. See more at newark.com

How may we help you today?

Website

newark.com

Email

order@newark.com
quote@newark.com

Phone

1.800.463.9275
M-F 7:00 AM – 8:00 PM (EST)

Fax

1.888.551.4801

eProcurement Systems

We can link with any eProcurement system and our dedicated e-team will facilitate your implementation.
email: eproc@newark.com

Same-Day Shipping

newark.com/shipping
Domestic: Order M-F by 9:30 PM (EST)
Export: Order M-F by 6:00 PM (EST)
In-stock products normally ship the same day

No Minimum Order Fees



You Can Find Us at...



An Avnet Company © 2020 Premier Farnell Limited. All rights reserved. Newark is a trading name of Premier Farnell Limited. This information is of a general nature and is not intended to address the circumstances of any particular individual or entity. No one should act on such information without appropriate professional advice. Please see our website, newark.com, for updated information. The information and pricing contained on our website supersedes the information contained in any printed catalog or other publication. Printed in the U.S.A. WF-2109723

IP RATING OVERVIEW & NEMA RATINGS FOR ENCLOSURES

IP RATING OVERVIEW

IP (Ingress Protection) ratings consist of the letters IP followed by two digits and an optional letter. The first digit refers to the level of protection against hazardous parts and the ingress of solid foreign objects. The second digit refers to the level of protection against the ingress of water. This standard provides engineers with more detailed information regarding the protection status of a product than vague terms like waterproof. Below is a brief table outlining some of the common IP ratings that you'll see across our web site. We do offer products with ratings not listed below.

IP Rating	Water Protection	Dust Protection
IP65	Water at 12.5 liters per minute through 6.3mm nozzle from any direction	Total dust ingress protection
IP66	Water at 100 liters per minute through 12.5mm nozzle from any direction	Total dust ingress protection
IP67	Submersion into water up to 1 meter deep for amount of time specified by manufacturer	Total dust ingress protection
IP68	Permanent submersion beyond 1 meter into water of depth stated by manufacturer	Total dust ingress protection
IP69K	Water at 80-100MPa (megapascal) and 14-16 liters per minute from four angles while the device is rotated at 5RPM	

NEMA RATINGS FOR ENCLOSURES

Indoor Nonhazardous Locations

The National Electrical Manufacturers Association (NEMA) provides a popular standard for protective enclosures. These conditions include ingress of water and foreign objects (e.g. dust or fibers), but go beyond IP code, accounting for corrosive agents and various gases and atmospheres. The table provides a brief description of each level of protection, which NEMA specifies with a NEMA Enclosure Type Number.

Provides a Degree of Protection Against the Following Environmental Conditions	Enclosure NEMA Type									
	1	2	4	4X	5	6	6P	12	12K	13
Access to hazardous parts	x	x	x	x	x	x	x	x	x	x
Ingress of solid foreign objects (Falling dirt)	x	x	x	x	x	x	x	x	x	x
Ingress of water (Dripping and light splashing)		x	x	x	x	x	x	x	x	x
Ingress of solid foreign objects (Circulating dust, lint, fibers, and flyings **)			x	x		x	x	x	x	x
Ingress of solid foreign objects (Settling airborne dust, lint, fibers, and flyings **)			x	x	x	x	x	x	x	x
Ingress of water (Hosedown and splashing water)			x	x		x	x			
Oil or coolant seepage								x	x	x
Oil or coolant spraying and splashing										x
Corrosive agents				x			x			
Ingress of water (Occasional temporary submersion)						x	x			
Ingress of water (Occasional prolonged submersion) protective enclosures.							x			

Outdoor Non-hazardous Locations

Provides a Degree of Protection Against the Following Environmental Conditions	Enclosure NEMA Type									
	3	3X	3R	3RX	3S	3SX	4	4X	6	6P
Access to hazardous parts	x	x	x	x	x	x	x	x	x	x
Ingress of water (Rain, snow, and sleet **)	x	x	x	x	x	x	x	x	x	x
Sleet		x	x	x	x	x	x	x	x	x
Ingress of solid foreign objects (Windblown dust, lint, fibers, and flyings)			x	x		x	x	x	x	x
Ingress of water (Hosedown)			x	x	x	x	x	x	x	x
Corrosive agents			x	x		x	x			
Ingress of water (Occasional temporary submersion)								x	x	x
Ingress of water (Occasional prolonged submersion)										x



Your trusted partner
in automation

Omron's ruggedized water-, dust- and oil-resistant industrial automation components maximize uptime and guarantee continued productivity and safety.



E3AS
Photoelectric sensor

Distance-settable time of flight (TOF) and background suppression (BGS) photoelectric sensors with exceptionally long sensing range of 50 to 1,500 mm, stable detection for various targets and compact body.

[Search 51AH5431 at newark.com](#)

- Reliably detect targets, including those with variable features.
- Allow users to choose between long-range and short-range sensors to fit their sensing needs.
- IO-Link helps with sensor configuration and enables IIoT applications. The E3AS-F family's distance output can be monitored via IO-Link.
- Reduce the frequency of shutdowns. The E3AS sensors are ruggedized for harsh environments thanks to their IP69K washdown resistance, IP67G oil resistance, and Ecolab certification for detergent resistance.
- Improve setup times. The sensors' user-friendly design, single each button, and IO-Link configurability make setup easy.



E2E NEXT
Proximity sensor

The E2E NEXT DC 3-wire weld splatter resistant series of proximity sensors offer latest generation sensing distances that significantly reduce target contact, solve size limited applications with smaller form factor sensors, have oil resistance, and provide real-time condition monitoring with IO-Link in welding applications.

[Search 28AH9021 at newark.com](#)

- With high-brightness LED, indicator is visible 360° around.
- Only 10 seconds to replace a sensor with the Quick fix (Mounting Sleeve).
- Cables with enhanced oil resistance have 2-year oil resistance
- IP69K compliant for water resistance and wash resistance
- UL certification (UL60947-5-2) and CSA certification (CSA C22.2 UL60947-5-2-14)
- All PNP models come standard with IO-Link



F3SG-SR Series
Safety light curtain

The Omron's new F3SG-SR series safety light curtain has a standardized yet flexible design that allows manufacturers to comply with safety standards and make the most of their flexible production lines while ensuring full protection for equipment operators. Water-proof and resistant to cutting oil.

[Search 40AH0354 at newark.com](#)

- Conforms to major international standards
- Environmental resistance and rugged structure for use in
- From finger protection to body protection
- Flexible height model for easy integration into machines and lines
- For diverse applications, from simple protection to data utilization
- IP67, IP67G rated



D4A-N
Limit switch

The limit switch with better seal, shock resistance, and strength. D4A-N provides excellent durability with a wide operating temperature of -40°C/F- 100°C/212°F (standard type).

[Search 99F8608 at newark.com](#)

- A double seal on the head, a complete gasket cover, and other features ensure a better seal (meets UL NEMA 3, 4, 4X, 6P, 12, 13).
- Wide standard operating temperature range: 40C to +100C (standard type).
- Models with fluoro-rubber available for greater resistance to chemicals.
- Block mounting method also reduces downtime for maintenance.
- DPDT, double-break models available for complex operations.
- Approved by UL, CSA, and CCC (Chinese standard).
- IP67 rated

Visit Newark online: <http://www.newark.com/omron-industrial-automation> • email: order@newark.com • 1.800.463.9275

RELAYS, PUSHBUTTONS, INDICATORS & MORE

Syr-Line Universal Digital Timer



LED screen, multifunction, precise time configuration, optional features: password setting and time limit setting. Programmable without its power supply, wide time range

Search

[51AH7696](#) at [newark.com](#)

Contactor, 200 A, With Flange, 12 VDC, SPST-NO, 1 Pole



The 586-902 is a 1-pole Contactor with standard bracket, 200A contact current rating, 12VDC coil voltage and flange mount. SPST-NO contact configuration, 21Ω Coil resistance at 25°C temperature

Search

[35M1913](#) at [newark.com](#)

FL1F Smart Relay



DEC SmartRelay meets your demands from all small-scale applications by offering more powerful hardware, a new display and full communication options via Ethernet

Search

[72Y0249](#) at [newark.com](#)

Series 45 IP69K Rated Pushbutton



Series 45 pushbuttons combine rugged construction with an attractive design. Featuring IP69K protection, penetration by dust and liquids is prevented, even under the most adverse conditions

Search

[98Y4476](#) at [newark.com](#)

Series 82 Pushbuttons – New Stainless Steel SUS 316L Version



EAO's new stainless steel version of its ever-popular Series 82 features high-quality stainless steel SUS 316L to reliably protect against corrosion and alkaline cleaning agents

Search

[41AH6843](#) at [newark.com](#)

PB300 Series Pushbutton Provides Long Travel for Double Action



Momentary function, PCB mount, long travel – 2.0mm, SPST or SPD. Key feature – SPDT double action; mid-travel for actuation at 600 gf; continue pressing for actuation at 1150 gf

Search

[49Y5667](#) at [newark.com](#)

Square Pushbutton Provides Threaded Mount and IP67 rating.



Square pushbutton with nylon housing, threaded panel mount, IP67 rating for dust and moisture protection, long-life expectancy, 100,000 operating life cycles, 630gf +/- 130 grams

Search

[47AC2909](#) at [newark.com](#)

Explosive Atmosphere Pushbutton – Green with Boot



XB4BP31GEX – Round industrial pushbutton switch, Harmony XB4 Series, 22.5 mm, SPST-NO, momentary

Search

[07AH1242](#) at [newark.com](#)

SSA-EB Series Lighted Emergency Stop Push Buttons



Rugged design; easy installation with no assembly or individual wiring required
 • Push-to-stop, twist-to-release, or pull-to-release operation per IEC60947-5-5

Search

[79AC9712](#) at [newark.com](#)

WLS27 LED Strip Light for Harsh Environments



Fully encased in a shatterproof, chemically resistant copolyester housing with a cascading option. Rated IP66, IP67, and IP69K for washdown applications. Color options combine illumination and indication

Search

[76AC1136](#) at [newark.com](#)

F3SG-SR Series Safety Light Curtain



The New F3SG-SR Series Safety Light Curtain has a standardized yet flexible design that allows manufacturers to comply with safety standards and make the most of their flexible production lines

Search

[40AH0367](#) at [newark.com](#)

671 Series Panel Mount Indicator



Green sealed 1" LED Panel Indicator with black anodized aluminium housing and raised diffused lens. Sealed to IP67, vibration and vandal-resistant, and suitable for harsh environments

Search

[93Y2261](#) at [newark.com](#)

Linear Solenoid, Push or Pull



This solenoid provides a long-life and rugged design with linear actuation. It is ideal for high force and short-stroke applications

Search

[20M1701](#) at [newark.com](#)

STA Tubular Solenoid



The STA Series provides high resistance to shock and vibration to withstand extreme ambient conditions and is also available in magnetic latching versions

Search

[40AH1364](#) at [newark.com](#)

Low Profile Linear Solenoid



Conical-faced designs extend the useful range of solenoid to provide higher forces for strokes typically over 0.06-inch. Provides long-life and rugged design. Is ideal for high force and short-stroke applications

Search

[20M1767](#) at [newark.com](#)

FANS, CONTACTORS, REED SWITCHES & SWITCHES

IP68 Rated 4300U Series DC Axial Fan

ebm



60x25 mm compact fan, fully encapsulated against water and dust, motor protection against reverse polarity/locking, air exhaust over struts

Search
[67H5088](#) at [newark.com](#)

IP68 Rated 3300NU Series DC Axial Fan

ebm



92x38 mm compact fan, fully encapsulated against water and dust, motor protection against reverse polarity/locking, air exhaust over struts

Search
[41Y1541](#) at [newark.com](#)

IP69K Axial Fan - ONLY available from NMB!

NMB



Highest IP Protection available with auto restart/polarity protection and -10°C ~ +70°C allowable operating ambient temperature range

Search
[99Y7375](#) at [newark.com](#)

124-902 - Contactor, 100 A, With Flange, 12 VDC, SPST- NO, 1 Pole

White
Rodgers



1-pole heavy duty DC Power Contactor, SPST-NO contact configuration, silver alloy contact. 100A continuous and 400A inrush current. 4 isolated terminals. #10-32 UNF-2A thread coil terminals.

Search
[35M0121](#) at [newark.com](#)

XTSE Safety Contactors Help Protect people and Equipment

EATON



Eaton's XTSE Safety Contactors are SIL, SUVA, UL, CSA, and CE certified with IEC 60947 Safety Standards. Contactors available from 7 to 150 amps

Search
[60AC6740](#) at [newark.com](#)

XTSE Safety Contactors Help Protect people and Equipment

EATON



XTSE Safety Contactors are SIL, SUVA, UL, CSA, and CE certified with IEC 60947 Safety Standards. Contactors available from 7 to 150 amps

Search
[60AC6761](#) at [newark.com](#)

DC1 Drives - Energy Savings Motor Control with AC Drives

EATON



DC1 AC Drives provide significant energy and cost savings. The DC1 drives provide speed control and significantly reduce electrical costs. They are available in both Single and Three phase applications

Search
[78AC3525](#) at [newark.com](#)

FLEX-14 Series 14mm Reed Switch

Littelfuse



A sub-miniature, normally open switch with a 14.00mm long x 2.28mm diameter (0.551" x 0.090") glass envelope and longer than standard, flexible, easily formed leads, capable of switching 200Vdc at 10W

Search
[72R4593](#) at [newark.com](#)

59170 Series Sub- Miniature Overmolded Reed Switch

Littelfuse



Capable of switching up to 200Vdc at 10W. Well suited for position and limit sensing, security, and door/window alarm systems

Search
[89K7545](#) at [newark.com](#)

MDSM- 10 Series 10.2mm Surface Mount Reed Switch

Littelfuse



Capable of switching 200Vdc at 10W. Ideally suited for reed relay applications, security, metering and limit sensing applications

Search
[38X7498](#) at [newark.com](#)

Single Pole Double Momentary Sealed Toggle Switch

SAFRAN



Safran sealed toggle switch products are sealed to IP68 and are suited for a wide range of commercial, industrial and military markets

Search
[50F1565](#) at [newark.com](#)

HS1T Interlock Switches with Solenoid

IDEC



Ideal for use on large doors and large equipment requiring strong locking force. Smallest in the industry with 5000N locking force. Rear unlock mechanical indicator allows the lock status to be identified easily

Search
[28AH8534](#) at [newark.com](#)

APEM KH Series Sealed Rocker Switches

APEM



Designed for harsh environments, the KH series rocker switches are protected against accidental actuation with a protection guard and sealed to IP69K

Search
[67AC6376](#) at [newark.com](#)

RGB LED Indicators

APEM



APEM Q series LED Indicators available in new customizable RGB colors and available in 10mm, 14mm, 16mm, 19mm & 22mm bezels

Search
[39AH8630](#) at [newark.com](#)

Propor- tional Hall Effect 2-axis Min- iature Thumb- stick with LEDs

APEM



APEM's TS series thumbsticks feature non-contacting Hall effects, 2-axis miniature controller with multiple actuator & linear output options. Above panel sealing up to IP69K

Search
[61AC4027](#) at [newark.com](#)

INDUSTRIAL CONTROLS, TIMERS & ENCLOSURES

4FE+2G SFP Managed Ethernet Switch



EKI-7706E-2F supports 4 Fast Ethernet ports, 2 SFP ports, and it is embedded with Advantech's IXM function, which benefits users with fast deployment and can dramatically save engineers time and costs

Search
57AC6297 at newark.com

15-ch Digital I/O Module



The ADAM-4051 features seven digital input channels and eight digital output channels. The outputs are open-collector transistor switches that you can control from the host computer

Search
47M1645 at newark.com

Basic Line Unmanaged Industrial Ethernet Switch

Weidmüller



Unmanaged Plug & Play switches in a robust IP 30 protected aluminium housing. The equipment can be delivered with Fast Ethernet and Gigabit Ethernet ports – an economical solution for industrial Ethernet

Search
44T5720 at newark.com

MICRO SWITCH™ Heavy-Duty Limit Switches HDLS Series

Honeywell



NEMA/IP sealing features twin shaft seals for an extra measure of protection. Ideal for applications with demanding indoor and/or outdoor environments, where they may be subjected to shock or vibration

Search
23F4784 at newark.com

Severe Duty Limit Switch



Severe duty mill limit switch with rotary head, SPDT-DB snap action contacts, 20 amp rated for applications requiring extra heavy duty contact ratings, or higher operating and reset forces

Search
17B1689 at newark.com

MD Enclosed Motor Disconnect Switch



3 P, 30 A, Motor Disconnect Switch with NEMA 4X Enclosure serves as a local on/off switch for a motor when the motor branch circuit protection is in a central enclosure

Search
52T4374 at newark.com

4980 Programmable Repeat Cycle ON - OFF Timer



The model 4980 is a microcontroller based ON - OFF timer with digital display of timing. It controls a set of high current output contacts in accordance with a pre-programmed ON-OFF schedule

Search
88K1414 at newark.com

2600A DIP Switch Adjustable ON - OFF Cycling Timer



The 2600SA is an ON/OFF timer controlling a set of DPDT relay contacts. The timer is available in both AC and DC voltages, and all models contain two 12 position DIP switches for setting the time delays

Search
88K2126 at newark.com

438U Series Universal Time Capsule® Delay-On-Make Timer



From the creator of the Original Universal Time Capsule®. Fully encapsulated US manufactured delay-on-make timer. Over 1M Units sold for Harsh Environments. 10A switching capability, C-UL-US

Search
88K2159 at newark.com

HyShed IP69K Enclosure



Engineered specially to withstand sanitary washdown cleaning procedures. Features 15-degree sloped top which facilitates runoff of water and a FDA-grade silicone gasket helps resist bacteria growth

Search
84AC6178 at newark.com

NBF Series NEMA 4x/IP66 Boxes



All plastic hinged lid polycarbonate or ABS boxes with clear or opaque covers. Choice of indoor or outdoor version, quick mods are available

Search
73R7991 at newark.com

Mod-ern-Style IP68 Polycarbonate Enclosure



Strong die-cast box tested to exceed IP68 requirement so use in wet, underwater or dry environments. Available in natural or black finish

Search
72Y0535 at newark.com

AN-A Die Cast Aluminum NEMA 4x/IP68 Box



Hammond's 1557 Series offer IP68 protection and versatility. They can be used on a tabletop or two different wall-mount configurations

Search
39AH9611 at newark.com

IP68 / NEMA 4X & 6P Enclosures



Hammond's 1554 Series enclosures are ideally suited for mount PC boards in harsh environments including submersion

Search
98H1103 at newark.com

UL Type 4X Stainless Steel Enclosure



Eclipse Junior provides protection for equipment in very wet environments, or in specific applications where corrosion may be a problem

Search
89W2206 at newark.com

SENSORS, POTENTIOMETERS & MORE

Q4X Laser Distance Sensor



FDA-grade stainless steel housing rated to IP69K for harsh environments. Superior performance to detect sub-millimeter changes in distance. Reliable detection across a variety of colors, materials, and surfaces"

Search

[39Y8666](#) at [newark.com](#)

INIR Refrigeration Sensor



Designed with the latest technology, using a microcontroller with an ARM7 core and via software design the necessary techniques have been implemented to increase the reliability of the device

Search

[42AH1235](#) at [newark.com](#)

2JCIE- BL01-P1 PCB Bluetooth Environment Sensor



2JCIE series comes in a PCB-type package capable of sensing temperature, humidity, light, barometric pressure, and sound noise, while also calculating a UV index, discomfort index, and heat stroke risk level

Search

[72AC8842](#) at [newark.com](#)

Reflective Object Sensor



The OPB9001 PCB module takes the versatile and programmable OPB9000 reflective sensor and enhances its capabilities by integrating multiple features into a robust, small form factor for ease of use

Search

[38AH5861](#) at [newark.com](#)

High Performance Fiber Optic Trans- mitters



The OPF350A/OP-F352A fiber optic transmitters are high performance devices packaged for data communication links. Specifically designed to efficiently launch optical power into fibers

Search

[99AC0442](#) at [newark.com](#)

IP69K Rated Inductive Proximity Sensor



ICS Series Inductive Proximity Sensor, rated IP69K, M12 in diameter, 2mm sensing range, PNP NO output, 10-36VDC supply, M12 plug connection

Search

[91Y1179](#) at [newark.com](#)

IP69K Rated Capacitive Proximity Sensor



CA Series feature TRIPLESIELD PROTECTION, rated IP69K, M30 in diameter, 4-25mm adjustable sensing range, PNP NO+NC output, 10-40VDC supply voltage, 2M PVC cable connection

Search

[99Y7880](#) at [newark.com](#)

PX633A High Accuracy Submersible Pressure Sensor



PX633 Submersible Level Transmitter is designed for dealing with the most demanding level measurement conditions. The sensor adopts advanced microprocessor assures high precision measurements

Search

[32AH7878](#) at [newark.com](#)

E3AS time of flight (TOF) Pho- toelectric Sensor



Distance-settable Time of flight E3AS Series photoelectric sensors with exceptionally long sensing range of 50 to 1,500 mm, stable detection for various targets and compact body

Search

[51AH5431](#) at [newark.com](#)

PT100 RTD Sensor with M12 Connector



The PR-21 PT100 Class A RTD sensors feature 316L SS construction for vibration, strength and corrosion resistance. Available in a variety of mounting treads, probe diameters and lengths.

Search

[31AC5642](#) at [newark.com](#)

Rangeable Pressure Transmitter with Display



Industrial Pressure Transmitters feature IP67 rugged enclosure for industrial environments and LCD module to easily re-scale output signals. Offered in gauge & absolute ranges.

Search

[28AH0533](#) at [newark.com](#)

High Accuracy Submersible Pressure Transmitter



Submersible Level Transmitter with 4-20 mA output for harsh industrial environments features error compensation assuring 0.1% accuracy. Available in ranges up to 300 psi.

Search

[32AH7876](#) at [newark.com](#)

Series RG Two Point Pull Handles



Two-Point or Pull Handle and pocket handle varieties available in phenolic, thermoplastic and thermoplastic overmold materials. Female insert, tapped thread, pocket & plain molded hole options available

Search

[12AC6577](#) at [newark.com](#)

16mm Rotary Potenti- ometer



TT Electronics' P160 Series of RoHS compliant rotary potentiometers feature metal shaft/bushing. The series has a 100,000 cycle life and multi-ganged version is available.

Search

[63M1595](#) at [newark.com](#)

Cermet Trimming Potentiome- ters



Model 67 series of cermet trimming potentiometers are highly reliable and have a long life. These multiturn, 3/8" square trimmers are sealed to be compatible with the aqueous PCB cleaning process

Search

[15M3800](#) at [newark.com](#)

REED SWITCHES, FUSES, POWER & MORE

Industrial DIN Rail Power Supplies TIB-EX Series

TRACO POWER



Next generation of 80 / 120 / 240 / 480 watt platforms with 90~95% efficiencies feature -40°C to +60°C full load operating temperature and UL508 / ATEX / UL Hazloc certifications

Search
23AH4389 at newark.com

259 Series Hazardous Area Safe-T-Plus Fuse

Littelfuse



The safe-T-Plus 259 Series offers a range of encapsulated fused designed to enable greater safety for operating electronic equipment within potentially explosive environments

Search
98K4422 at newark.com

SDU-A DIN Rail AC UPS

EMERSON SOLAHD



Provides protection from impulses and power interruptions with communications, wide temp range, cold start capability

Search
11AC9462 at newark.com

3000-4080W 3-Phase Input, 24V & 48Vdc Output Power Supplies

TDK-Lambda



Suitable for 400/440/480Vac Delta or WYE input, the TPS series is fully featured with voltage and current programming, PMBus communication, current share and warning signals

Search
98Y1786 at newark.com

Compact, High Performance SMD Fuse

SCHURTER



SCHURTER's time-lag fuse, UMT-H is UL approved upto 6.3 A at 277 VAC and up to 30 A at 250 VAC. VDE approval up to 16 A @ 250 VAC

Search
84Y6808 at newark.com

SDN-C Compact DIN Rail Power Supply

EMERSON SOLAHD



High Efficiency, diagnostic LED's, PFC, Sag Immunity, universal input offers highest performance. In stock and ready to ship today

Search
40M7848 at newark.com

50 to 1500W Long Life, Cost Effective Power Supplies

TDK-Lambda



The RWS-B series of industrial power supplies have a seven year warranty and extended field life due to conservative electrolytic capacitor temperatures

Search
41X4242 at newark.com

DTE06/10 Series 6W, 10W Encapsulated DC/DC Power Supplies

XP Power



The DTE06/10 series comes in chassis or din rail option, single or dual outputs 5.1V to 48VDC and a wide input 4:1 12V, 24V, 48VDC

Search
28AH0886 at newark.com

UniStar SB Series UPS

SPACO ENERGY



Perfect for protecting business critical servers, voice and data networks, and point of sale

Search
13AC7452 at newark.com

Ultra-compact EMC/RFI Filter for Three-phase Systems & Drives

SCHAFNER



Most compact and slim filter design in its class, exceptional attenuation performance. from 150khz tp 30mhz

Search
24W5219 at newark.com

DSR240 Series - 240W Ultra Slim 45MM DIN Rail Power Supply

XP Power



The DSR240 has 150% peak load for 3 sec, full load at 60C, comes in 24V and 48VDC out and has an operating ambient temp of -25C to +70C

Search
65AC5748 at newark.com

10C Series POWERSTAT® Variable Transformer

Superior Electric



Rated at 2.25A for constant current loads and 3.0A for constant impedance loads

Search
32M1435 at newark.com

Multi-stage EMI Filter With Excellent Attenuation

SCHAFNER



Two stage filter, current rating 1 to 20 A, optional medical versions (B type)

Search
06M3260 at newark.com

SCP-X IP67 Extreme Environment Power Supply

EMERSON SOLAHD



Delivering reliable distributed and remote field power to machine controls. Versatile mounting, quick change connectors. Class 2 listed

Search
83X9949 at newark.com

Crouzet Power Supply, Smaller Size, Better Performance

CROUZET



Suited for use with all Crouzet 24V DC products, range from 10-100W, wide voltage input ranges (84 to 264V AC), energy efficiency increased up to 90%, low no-load power consumption

Search
23AH8664 at newark.com

INTERCONNECT

UPT Connector Series




Based on the 26482 Series I, UPT is a plastic shell interconnect with a metal bayonet coupling system and crimp contacts

Search

[99Y7644](#) at [newark.com](#)

Micro-Bayonet Connector Series




Micro-B meets the requirements of today's electrical equipment for a connector with a small footprint, light in weight, high density insert patterns, and high reliability

Search

[52AC2549](#) at [newark.com](#)

Locking Power Cords for Standard AC Inlets




The locking feature is designed to prevent accidental disconnection of any equipment, like medical apparatus, servers, computers. Available also with any International plug

Search

[99AC3043](#) at [newark.com](#)

FCT Standard-Density Waterproof D-Sub Female Connector




Waterproof FCT D-Sub female connector provides IP67 protection in harsh environments. Machined contacts supply increased current-carrying capacity over stamped contacts. Delivers a 5.0A current rating

Search

[33AC8259](#) at [newark.com](#)

Squba 1.80mm Pitch, Sealed Wire-to-Wire Receptacle Housing




Squba receptacle housings offer an IP67-seal rating and carry up to 6.0A. With protected seals, the system delivers reliable power in a wide range of space-constrained applications

Search

[55AC8186](#) at [newark.com](#)

Sealed Industrial USB 3.0 Type A Receptacle and Plug Cordset




Improve performance and reliability in harsh-duty applications with Molex IP67 sealed Industrial USB 3.0 Type A Receptacle to USB Type A dual-ended, 0.8m length with other lengths available

Search

[83X6172](#) at [newark.com](#)

mPOWER™ 2.00 mm Pitch Ultra Micro Power System




Design flexibility as a two-piece system for power/signal applications. Up to 21 A per power blade. 2 – 5 power blades on a 2.00 mm pitch. 5 mm to 16 mm stack heights

Search

[95AC5512](#) at [newark.com](#)

Dura-Con™ Hermetic Connectors




Standard connectors with high performance hermetic seals

Search

[46AC0123](#) at [newark.com](#)

Rugged, High Quality Power Cords




A wide array of domestic and international power cords in stock and ready to ship today

Search

[81K8077](#) at [newark.com](#)

RJ45 Connectors




A wide range of RJ45 Connectors within multiple Platforms – 1x1, 1xN, 2xN, Side entry, top entry, offset and low profile

Search

[60AC3107](#) at [newark.com](#)

CTC Series Environmentally Sealed Cable-to-cable Interconnects




High performance, cost effective cable-to-cable solution for use in harsh environment applications

Search

[48AC9072](#) at [newark.com](#)

Universal Range – PUSH IN Wire Connection (A-Series)




Reduces connection times for solid wires and wires with crimped on wire-end ferrules

Search

[47AC3958](#) at [newark.com](#)

Sealed Connections with New Aquanex® Waterproof Micro USB




As part of an exciting new product line from GCT, the aquanex® waterproof range brings together high performance USB connectors with excellent IP rated sealing

Search

[21AH2936](#) at [newark.com](#)

3M™ IDC Ribbon Cable Socket




891 Series IDC Ribbon Cable Socket for .100" × .100" for .050" Pitch Cable

Search

[92F1490](#) at [newark.com](#)

USB 2.0 Combination MagJack® Integrated Connector Modules (ICM's)




An all in one solution, combining a RJ45 Ethernet port with a USB-A 2.0 connectors. This combination allows customers to stack or group one or two USB connectors into one robust, small form factor size

Search

[81AC4236](#) at [newark.com](#)

INTERCONNECT

Eaton's XB Series - DIN Rail Mount Terminal Blocks



Compact design terminal block with single feed screw connections. Many colors available including accessories for labeling, bridges, ground blocks

Search

[47T6251](#) at [newark.com](#)

Water-proof USB Type-C Connectors



Ideal for use in harsh environment applications where moisture is present

Search

[58AC0291](#) at [newark.com](#)

Mil Spec Connector Tools and Accessories



Connector assembly and maintenance tooling for military, aerospace, medical and telecommunication Industries

Search

[94Y5377](#) at [newark.com](#)

Cost Effective Power & Signal Distribution System



IP67 rated yellow cordsets are a cost effective power a& signal distribution system compatible with other industry standard mating connectors

Search

[47AC7636](#) at [newark.com](#)

Indoor / Outdoor Plastic or Metal Connectors rated up to IP69



The ecomate® Family of circular, multiway connectors provide an IP65-69k rating range (in mated condition) for indoor/outdoor industrial applications and feature robust, durable plastic or metal designs

Search

[73AC8458](#) at [newark.com](#)

Integrated Connector, Circuit Breaker and EMC Filter with IP67 Protection



SCHURTER's versatile DG12 series is IEC rated up to 10A/250 VAC. UL/CSA rated up to 15A/125/250 VAC UL/CSA. The EMC filter is rated 1A up to 10A with standard/high inductance

Search

[95AC5478](#) at [newark.com](#)

IP67 Industrial Ethernet M12 X-code to RJ45 panel feed-through adapter



METZ CONNECT's M12X/RJ45 feed-through adapters provide high performance, 10 GBit Ethernet cabling and 10 GBit device connection in communication cabling and automation and control equipment

Search

[37AC4285](#) at [newark.com](#)

Series 500 ZD Connectors



0.098" (2.5mm) Pitch for 6.25 Gbps/pair. See additional details at [newark.com](#)

Search

[78AC5793](#) at [newark.com](#)

New High Current 13A VAL-U-LOK Connectors



Offer a higher 13A maximum current rating on 4.2mm centerline spacing

Search

[23AH8940](#) at [newark.com](#)

M Series Circular Connectors



Push-in, IDC, Crimp Type Field Installable. In stock and ready to ship today

Search

[21AH2930](#) at [newark.com](#)

Triton Grounding Jumper Solutions



UL-certified off-the-shelf Triton Grounding Jumpers enable the safe management of high-power applications and customized versions offer variable lengths and terminations

Search

[52AH3559](#) at [newark.com](#)

Medium Power Distribution Blocks, 2 & 3 poles



BlockMaster's new HP Series (300V / 50A) Terminal Blocks, available in 2 or 3 poles. Good for transition larger gauge #2-14 to internally distribute #10-14-gauge secondary circuitry (thru .250" Q.C.)

Search

[51AH5782](#) at [newark.com](#)

VULCON® M12 Pigtail Connectors



M12 pigtail connector configurations 4 pin, 5 pin, & 8 pin. IP67 Rating

Search

[17AH5161](#) at [newark.com](#)

AC Receptacle 701W-X2/04



This IEC 60320 C14 receptacle is equipped with snap-in mounting tabs and 0.250" quick disconnect terminals, allowing for very fast installation on the production line

Search

[17B6789](#) at [newark.com](#)

BKZ Series Locking Power Jacks & Plugs





The new BKZ series from Switchcraft solves one of the largest issues with typical DC power jacks: accidental disconnect

Search

[99AC7763](#) at [newark.com](#)

INTERCONNECT

Nano-Fit Off-the-Shelf (OTS) Overmolded Cable Assemblies

Nano-Fit Double-Ended, Overmolded Cable Assemblies with strain relief offer off-the-shelf and customized versions with various circuit sizes and lengths.

Search
[58AC8104 at newark.com](#)

Off-the-Shelf (OTS) Mega-Fit Overmolded Cable Assemblies




Molex delivers off-the-shelf and customized Mega-Fit Overmolded Cable Assemblies in multiple circuit sizes and lengths, combining rugged signal connection with a user friendly interface.

Search
[58AC8093 at newark.com](#)

Right Angle USB SealJack Connectors




Reliability and functionality are a necessity when Ethernet moves outside the typical office environment. These sealed connectors protect against moisture and other harsh environmental factors

Search
[99AC3222 at newark.com](#)

Twist-Lock™ Plugs & Receptacles




Hubbell Twist-Lock™ plugs and receptacles are recognized as the industry standard for locking devices because of their long history of durable construction and innovative safety features

Search
[38F504 at newark.com](#)



Hubbell Insulgrip® Plugs and Connectors




The tough nylon body provides impact and chemical resistance. The durable and powerful offsetting cord grip clamps on individual conductors and outer cord jackets prevent strain on the terminals

Search
[32F750 at newark.com](#)



Mill-Max Zero Profile Press-Fit Receptacles

Mill-Max now offers even more variety by adding 10 new receptacles capable of accepting a broad range of mating lead diameters to suit a variety of interconnect requirements

Search
[95AC5307 at newark.com](#)



Entrelec SNK Series Terminal Blocks and Accessories

The innovative SNK series is available in PI-Spring (Push-In and Spring), screw clamp and pluggable technologies with common accessories. Qualified for worldwide applications and severe environments

Search
[70AC8773 at newark.com](#)

M12 X-Code Right Angle Connectors

Extremely ruggedized M12 connectors for field assembly, provides 10Gb/s data speeds in a right angle connector that safely and reliably supports communication in harsh environments

Search
[10AH2653 at newark.com](#)

Deutsch 369 Series Connectors




TE DEUTSCH 369 series connectors were developed to provide a range of high reliability, lightweight, compact, and cost-efficient connectors suited to aerospace, and other harsh environment applications

Search
[30AH0145 at newark.com](#)

Series 3 Circular Connectors with Threaded Joint M16




Wide range of parts, 3-14 poles, with and without 360° shielding. Compatible mating acc. to IEC 61076-2-106 and IEC 60130-9. Easy mounting with solder or crimp technology

Search
[23AH4188 at newark.com](#)

Cam-Lok™ J-Series E1016 Plugs




Double set screw elastomeric, non-vulcanized male and female plugs

Search
[52AC2446 at newark.com](#)

97 Series Connectors with Gray ZnNi Plating




Gray Zinc/Nickel plating provides an ideal RoHS compliant solution for harsh, high corrosive environments

Search
[54AC6859 at newark.com](#)



MTMM Series 2.00 mm Variable Post Height Terminal Strips




Industry's largest variety of low profile pin counts, terminal lengths and options up to four rows and 200 total pins

Search
[20W4379 at newark.com](#)

MIL-DTL-24308 D-Sub Connectors

Qualified to MIL-DTL-24308, Amphenol's D-Sub Connectors are subminiature rack & panel type connectors with polarized shells

Search
[56W1085 at newark.com](#)

New IP67 Cat5e/6 Dual-Use Waterproof Ethernet Cables




The innovative design of our new IP67 waterproof cables allows them to be used with IP rated receptacles for a watertight seal or they can be used with standard RJ45 jacks

Search
[60AC7086 at newark.com](#)

INTERCONNECT

Field Installable N Type Connector

Amphenol® RF



Can be terminated tool-free with no advanced skill and is ideal for a wide variety of applications including antennas, base stations, instrumentation and broadcast solutions

Search
[72AC9932 at newark.com](#)

2.2/5 Coaxial Straight Jack for RG405, 0.085" Semi Rigid

Amphenol® RF



The 2.2/5 series is lightweight and can accommodate thick, low loss cables up to a half inch. The robust design makes these connectors ideal for both indoor and outdoor applications

Search
[33AH9857 at newark.com](#)

N-Type Straight Plug to N-Type Bulkhead Jack on LMR 400

Amphenol® RF



Amphenol RF's line of ruggedized cable assemblies are engineered for superior performance in harsh environments. These assemblies are fully submersible and designed to withstand corrosion

Search
[02AH5745 at newark.com](#)

SMPM Socket D38999 Contact (Size 12) for .085 Cable

SV Microwave



SV Microwave offers DC to 40 GHz high frequency size 8, 12 and 16 coaxial contacts for the D38999 Series III housing and standard inserts

Search
[43AC7536 at newark.com](#)

2.92mm Female to Female Bulkhead Hermetic Adapter

SV Microwave



SV offers a wide range of IP67 and IP68 waterproof interconnects designed to withstand harsh elements such as high pressure, vacuum applications and the prevention of liquid or gas leakage

Search
[84AC4141 at newark.com](#)

SMPM Male to SMA Female Bulkhead Sealed Adapter, FD

SV Microwave



SV offers a wide range of IP67 and IP68 waterproof interconnects designed to withstand harsh elements such as high pressure, vacuum applications and the prevention of liquid or gas leakage

Search
[84AC4142 at newark.com](#)

2.92mm Male to 2.92mm Male 12" Cable Assembly for .047 Cable

SV Microwave



SV offers a complete line of fixed length, high frequency cable assemblies utilizing SMA, 2.92mm, 2.4mm, SMP, SMPM & SMPS connectors on flexible Ø.047 and Ø.085 cable types

Search
[41AC9234 at newark.com](#)

2.92mm Female Solderless LiteTouch PCB Connector, 2 Hole

SV Microwave



Meets the industry need for high performing, highly reliable solderless connectors for precision thin substrate mounting. Current configurations include 2.92 mm, 2.4 mm, and SMA versions

Search
[58AC8075 at newark.com](#)

1.85mm Connectors - 67 GHz with VSWR Performance to 1.20:1

Johnson



Delivers superior signal integrity in the most demanding environments. Easy to assemble and dis-assemble to a PCB, can be connected with solder or solderless, and adjustable to varying board thicknesses

Search
[60AC6729 at newark.com](#)

2.4mm Coax Connectors

Johnson



Max frequency of 50GHz, available in end launch and three mounting flange configurations

Search
[81F4452 at newark.com](#)

EMI/RFI Shielded Heat Shrink - ShrinkMate™

ShrinkMate®



A cost effective heat shrink solution that protects wire from signal interference

Search
[85AC0871 at newark.com](#)

Adhesive Mount Adjustable Cable Clamp

ESSENTIA COMPONENTS



Adjustable clamp that allows user to ratchet down on cable. Adhesive mount for easy application

Search
[28AH1144 at newark.com](#)

Adhesive Mount Cable Tie Holder

ESSENTIA COMPONENTS



Holds 18 Lb cable ties in any 4 directions. Adhesive mount for easy application

Search
[28AH1171 at newark.com](#)

Locking Snap In Circuit Board Support

ESSENTIA COMPONENTS



Both ends easily snap into pre-drilled holes by hand. Strong, dependable grip

Search
[28AH1214 at newark.com](#)

Nylon Snap Rivet

ESSENTIA COMPONENTS



Easily pushed into place by hand. See more nylon hardware at newark.com

Search
[69AC6573 at newark.com](#)

WIRE MANAGEMENT











WAGO 221 Lever-Nut



WAGO's new superstars for electrical installations allow solid, stranded and fine-stranded wires to be connected faster, more reliably, while minimizing the amount of space in junction boxes. They are 40% smaller than the 222 series lever connectors. The transparent housing allows visual inspection for correct wiring. There are also test ports at the front and rear of the connector. Ideal for Industrial, Communications & Networking, Lighting, Security, Signalling, HVAC applications

Search

[71Y8326](#) at [newark.com](#)

Pan Steel® Self Lock Stainless Steel Cable Tie  <p>Withstands harsh environments. Excellent ultraviolet resistance and chemical resistance. -80 to 538°C operating temperature range. Non-flammable flammability</p> <p>Search 94F2792 at newark.com</p>	3M Secure Grip Wire Connectors  <p>Will electrically connect and insulate copper conductors in a pigtail application. The connector has a live spring for strong reliable connections</p> <p>Search 01AH2291 at newark.com</p>	Metal Screening Braid  <p>Premium performance grade. Provides exceptional protection for wire and cable harnesses from electromagnetic, electrostatic and radio frequency interference</p> <p>Search 94AC7775 at newark.com</p>	FlexTack Adhesive Cable Tie Mounts  <p>Deliver excellent mounting performance on flat, curved and moderately angled surfaces. Excellent performance in extreme environmental conditions for a wide range of indoor and outdoor applications</p> <p>Search 151-01527 at newark.com</p>	SCT Flame- Retardant, Adhesive- Lined, Semirigid Polyolefin Tubing  <p>Thick adhesive liner forms an effective barrier against fluids and moisture. Performs well at an extended temperature range in under-the-hood auto environments</p> <p>Search 72J5088 at newark.com</p>
Raychem Rayseal Repair Sleeves  <p>Large gauge cable repair sleeve is a high performance side-entry repair product for large gauge and power feeder cables with chafed or cracked insulation</p> <p>Search 18AC0925 at newark.com</p>	TMS-SCE Military Grade Heat Shrink Tubing  <p>Lightweight for aerospace applications; Military spec material & print performance, CSA Certified</p> <p>Search 41M0784 at newark.com</p>	BATTU TUBING Dual Wall Heat Shrink Tubing  <p>Designed for power cable to terminal applications in harsh environments. Moisture-resistant seal withstands common automotive fluids. Offers mechanical protection for increased product reliability</p> <p>Search 40AH0881 at newark.com</p>	P-Clamp - Enabling Next Generation Assembly  <p>Quick install, flexible design, ergonomic. The new "tool-free" standard in wire and cable management. P-Clamp provides a light, fast, and efficient solution to mounting cable harnesses</p> <p>Search 40AH2025 at newark.com</p>	CM-SCE- TP Military Grade Cable Markers  <p>Thermal transfer printable and highly flame resistant - excellent resistance to burning (Oxygen Index 35%)</p> <p>Search 17M9922 at newark.com</p>

TOOLS & PRODUCTION SUPPLIES

ZEROS MOGTLKIT1N - Fume Extractor, 190 m³/h, 120 V, 120, Zero Smog TL Series



Fume extraction unit for up to 2 workplace. Includes Zero Smog® TL fume extraction unit, H13 particle filter and gas filter

Search
[01AC4444](#) at [newark.com](#)

WE1010NA - Soldering Station, WE Series, 120 V, 450 °C, 70 W



The digital 70 W WE soldering station is 40% more powerful than the WES / WESD station. This allows the iron to heat up faster and to provide a faster recovery time

Search
[45AC9886](#) at [newark.com](#)

WXR3001N - Rework Station, Multifunctional, 450 °C, 120 V



The WXR3001 is a Rework Station Set with WDH10 safety rests. Up to three 200W high performance tools can be operated simultaneously

Search
[40Y7488](#) at [newark.com](#)


WXR3002N - Rework Station, Multifunctional, 450 °C, 120 V



The WXR3002 is a multifunctional Rework Station used for soldering and desoldering of both large and small SMT components. LCD display simultaneously monitors all parameters

Search
[40Y7489](#) at [newark.com](#)

WXR3003N - Rework Station, Multifunctional, 450 °C, 120 V



The WXR3003 is a multifunctional Rework Station used for soldering and desoldering of both large and small SMT components. LCD display simultaneously monitors all parameters

Search
[40Y7490](#) at [newark.com](#)

WXD2020N - Rework Station, 120 V, US



Soldering and desoldering station, 2 channels 200 W (255 W), including desoldering iron WXDP 120, PDN desoldering nozzle plier and WDH 70 safety rest with brass tool

Search
[28W3381](#) at [newark.com](#)

WX2021N - Soldering Station, 120 V, 850 °F, 240 W, LCD Display, ESD Safe



Fine, thin WXMP soldering pencil is suited for work under a microscope. Large graphic LCD display can be viewed from all angles

Search
[39T0805](#) at [newark.com](#)

MX-500S - Rework Station, Dual Port, 240 V



The MX-500S is a Soldering and Rework System that has been reimagined, adding features and a new look to a bench top icon

Search
[23X5007](#) at [newark.com](#)

CV-5210 - Soldering Station Set, 240v, 125w, +55 °C Max Temperature



The CV-5210 from Metcal is a CV-5200 series connection validation digital soldering station. Delivers the right amount of power based on the requirements of the solder joint

Search
[13AC7485](#) at [newark.com](#)

BVX-201-KIT - Filter Unit, Kit, Extraction System, with 2 Flexible Arms, 1.2m



The BVX-201-KIT is a two operator, PRE-HEPA-GAS volume extraction system with two BVX-ARML designed to be used adjacent to the workbenches

Search
[29M6877](#) at [newark.com](#)

MX-PS5200 - Soldering Station Power Supply, For Metcal MX-5200 Series Systems



The MX-PS5200 is a soldering station Power Supply for use with MX-5200 series dual simultaneous soldering, desoldering and rework systems

Search
[48W5010](#) at [newark.com](#)


MX-5210 - Rework Station, Dual Port, 100-240VAC



The MX-5210 is a dual-port highly effective simultaneous Soldering and Rework System. Highly effective for soldering applications including lead-free, high mass components or boards

Search
[48W5011](#) at [newark.com](#)

MX-5241 - Rework Station, with TipSaver™ Workstand, 240 V



The MX-5241 is a dual-port simultaneous Soldering and Rework System with both the Advanced™ hand-piece and the precision tweezers. Users get maximum application flexibility for soldering and reworking

Search
[48W5014](#) at [newark.com](#)

PCT-100-11 - Hot Plate, Convection, 115 V, 450 W



The PCT-100-11 is a 115V Focus Pre-heater targets heat for improved speed and efficiency for high thermal demand applications, including lead-free

Search
[51M4853](#) at [newark.com](#)

HCT2-200-11 - Rework Station, HCT2-200 Series, 450 °C Max Temperature, 200 W, 110 V



The HCT2-200 was developed for very small surface mount component and package sizes (1206's and smaller) and low board densities

Search
[42AC9657](#) at [newark.com](#)

TOOLS & PRODUCTION SUPPLIES

170MN -
Cable Cutter,
Diagonal
Shear, Flush
Jaw, General
Purpose, 5"Length



The 170M from Xcelite is a diagonal flush cutter of 5" length. Flush cuts soft wire up to 20 AWG (0.8mm)

Search
50F172 at newark.com

CW8400
- Solder
Flux, Rosin,
Soldering, Pen
Applicator, 9 g



A pen for applying lead-free flux with precision and control. Applies a noncorrosive, halide free, no clean flux for high temperature, lead-free application

Search
29K6229 at newark.com

CW2200STP
- Coating,
Conductive,
Chemical, Grey, Pen
Applicator, 8.5g



The CW2200STP is a 8.5g CircuitWorks® Conductive Pen make instant highly conductive silver traces on circuit boards and are used in prototype, rework and repair of circuit boards

Search
00Z1497 at newark.com

24-6040-0027 -
Solder Wire,
60/40, 0.031"
Diameter, 190°C, 1lb



The 24-6040-0027 is a Solder Wire, Sn60+Pb40 Alloy. Rosin 44® is a high activity RA core flux designed for excellent instant wetting action, even on Nickel surfaces

Search
34C5648 at newark.com

609961 -
Solder Wire,
Crystal 400,
0.028" Diameter,
188°C, 8.818 oz



The 609961 is a no clean clear residue cored Solder Wire manufactured with a range of flux contents. Also applicable to repair operations carried out after a cleaning process

Search
15J8017 at newark.com

35622 -
Straight Probe,
Single Ended,
Nylon Finish,
ESD Safe, 6"



The 35622 is a 6-inch Point Blade Probe commonly known as a "black stick" nylon tool used in electronic repair and assembly. Ideal for opening plastic cases

Search
90H0265 at newark.com

44531
- Tweezer,
ESD, Straight,
Pointed,
Stainless Steel,
120 mm



Static Dissipative, ESD safe hypo allergenic tweezers made from Vommalloy. Special stainless steel, anti-magnetic and acid resistant

Search
28C1858 at newark.com

M4 4V
Cordless
Li-Ion
Screw-
driver Kit



Charger included - featuring 44 in-lbs of peak torque and a 21-position clutch with auto shut-off

Search
86T1091 at newark.com

2031-1 -
TechClean
Brushes
with 1/8inch
x 3/16inch
Horse Hair



Metal brush handle to ensure that the bristles remain intact during the most rigorous applications. Bristles made from horse hair

Search
68K7332 at newark.com

497AJN -
Vacuum Cleaner
Set, 120V, 6A,
ESD Safe, Type
2 Filter,
Detachable
Power Cord



The 497AJN is a 120V SCS Electronics Vacuum for high efficiency cleanup of most business equipment, including removing toner and dust. Backed with a one HP, 6A motor

Search
18M9349 at newark.com

SV-MPF2
- Vacuum
Filter, Type
2, Toner/
Dust



The SV-MPF2 is a SCS Type 2 Filter for Toner/Dust, is used in a wide variety of applications including removing toner from laser printers and copy machines.

Search
50F949 at newark.com

**91-GUARD-
US-01 -**
Ionizing Blower,
Overhead,
120 V, Aerostat
Guardian, 42.75 " x
4 " x 6.75 "



Simco-Ion's Aerostat Guardian Overhead Ionizing Blower provides superior static charge decay over an entire work surface area. Equipped with task lighting and an integrated heater

Search
07AH2007 at newark.com

4005105-01
- Ionizer,
Air Gun,
120V,164mm,
15V Ion Balance



The 4005105 is a high-performance Ionizing Air Gun designed for a wide variety of electronic manufacturing and assembly applications.

Search
08H0346 at newark.com

4003367 -
Ionizer,
Air, Benchtop,
120VAC,
70CFM, 35 cu.ft/
min, 5 sq.ft
Coverage



The 4003367 is a 120VAC single-fan bench top Ionizing Air Blower with polyester epoxy finished aluminum enclosure and stainless steel emitter points

Search
08H0344 at newark.com

V830SHC -
Task Stool,
ESD, on
Casters with
Footring,
Conductive Fabric,
Plastic Base



The V830SHC is an ESD Task Stool on casters with footring. Static-dissipative with a grounding brass drag chain. Pneumatic height adjustment 21" to 28.5"

Search
73P9738 at newark.com

TOOLS & PRODUCTION SUPPLIES

8507 - ESD Field Service Kit, Portable, Dual Conductor Wrist Strap, Ground Cord, Monitor



The 8507 is a Portable Field Service Kit with a SCS wrist strap monitor 725 bundles together 2-static control product to gives a field technician the same working environment as a worker in a facility

Search

[90B4103](#) at [newark.com](#)

ASK-32370 DESCO - Dissipative Mat, 2 Layer, Statfree B2 Series, Vinyl, Blue, 24" W x 30ft L



Static Protection Mat with non-skid foam nitrile butadiene rubber tray liner. Roll Mat designed to provide a path to ground and eliminate static charge generation

Search

[71Y6180](#) at [newark.com](#)

09183 - DESCO Wrist Strap, Anti-Static, Elastic, MagSnap, Jewel Series



Jewel® MagSnap adjustable wrist strap. Magnetic connection between wrist band and coil cord

Search

[20T7239](#) at [newark.com](#)

19246 - DESCO ESD Tester, Workstation Monitor for 2 Operator and 2 Work Surface



Dual operator workstation continuous monitor with satellites. Dual station continuous monitor for 2 operators and 2 work surfaces

Search

[71T8256](#) at [newark.com](#)

BMP21-PLUS BRADY - Label Print- er, Thermal Transfer, Alphabetical Keyboard, 203 dpi Resolution



The BMP21-PLUS is a portable Label Printer, all-in-one labeler for voice/datacom, electrical and general industrial teams. With label materials designed specifically for harsh environment

Search

[55X1824](#) at [newark.com](#)

3273/10 - MAJESTIC Gloves, Disposable, Powder Free, Nitrile, Large, 100 Pack



Disposable Nitrile Gloves Large - 100 Pack. Textured for added grip

Search

[45M6244](#) at [newark.com](#)

500-754- Mitutoyo 20 - Digital Caliper, IP67, 12"/300mm, 0.01mm Resolution



This IP67 ABSOLUTE digimatic caliper allows reliable measurements in a wide range of situations. Can be used in workshop conditions exposed to copolant, water, dust or oil

Search

[06P1062](#) at [newark.com](#)

26501-LED-8D AVEN - Magnifier, LED, 3X, Magnification, 45 ", Arm Length



The 26501-LED-8D is a ProVue 8-diopter LED Magnifying Lamp with 45-inch adjustable arm length. Reduces eye strain and vision fatigue for high-volume industrial users

Search

[28Y7449](#) at [newark.com](#)

FPM-50 - JONARD TOOLS Fiber Optic Tester, MADE FOR LIFE®, Fibre Optic, Indium Gallium Arsenide



An intelligent fiber optic power meter designed to measure wavelengths with high precision. It is used for absolute and relative power measurements.

Search

[45AC7136](#) at [newark.com](#)

TCMB100/ Weller ST - Tool Kit, Polyethylene Storage Case, 86 Piece



The TCMB100/ST is a 86-piece Professional Tool Kit for technicians, servicemen and field engineers. The TCMB series tool case is super-tough, black polyethylene with black anodized aluminium hardware

Search

[50F1839](#) at [newark.com](#)

576TX - Weller Cutter, Tapered and Relieved, 4.25 ", Super Full Flush, 0.012 "



The 576TX is a tungsten-carbide diagonal tapered/relieved Tip Cutter for use with stainless steel wires, catheters, coiled wires. This is the narrowest head shape

Search

[83F4089](#) at [newark.com](#)

020440 MOORE - Torque, Adjustable, 183mm Length



The 020440 is a 1/4-inch female hex externally adjustable Torque Limiting Screwdriver offers different setting options for applications that require more than torque value

Search

[49M1951](#) at [newark.com](#)

11063W - KLEIN TOOLS Wire Stripper 22-8 AWG / 0.34-6mm² Capacity, 6.6"



Klein Tools' popular Katapult® tool is now a stripper and cutter, too. Use the built-in cutting hole to cleanly cut 8-20 AWG solid and 10-22 AWG stranded wire

Search

[04X3908](#) at [newark.com](#)

C-PD914DD 3M - Wipe, Sorbent, 14.5 " x 9.25 ", 25 Pack



High capacity sorbent pads have a low profile design allowing them to be placed in tight areas. Great for cleaning up spills or wiping down contaminated areas

Search

[08X5456](#) at [newark.com](#)

1900-Storage EABE Cabinet, Fire Safe, Reinforced, Self Closing, 17.5 " x 18 " x 17.25 "



This bench top safety storage cabinet is ideal for storing your flammable liquids and supplies. Adjustable galvanized steel shelves hold 350 lbs. to meet all your needs

Search

[61T4162](#) at [newark.com](#)

TOOLS & PRODUCTION SUPPLIES

D5S-6 - Contact Cleaner, 5 oz



Contact Cleaner is rejuvenator unique contact cleaner, conductivity enhancer and lubricant. Chemically improves metal-to-metal connections and contacts

Search
[08H0311 at newark.com](#)

RSF-R80-2 - Solder Flux Jar, 56g



Rosin Soldering Flux for electrical and electronic soldering applications. The mildly-activated rosin flux is considerably more active than water-white rosin.

Search
[77M8009 at newark.com](#)

DeoxIT® L260 Grease Spray



For mechanical and electrical devices and equipment that require precise lubrication. A lithium grease with unique additives to enable it to adhere and stay on the surfaces it is applied to

Search
[95Y3828 at newark.com](#)

Kon- form® SR 10oz



Silicone conformal coating. Konform® SR provides maximum flexibility for extreme temperatures. Ideal protection for both rigid and flexible printed circuit boards

Search
[00Z1201 at newark.com](#)

Chemtronics ES820L IPA Isopro- pyl Alcohol 8 fl oz



ES820L IPA Isopropyl Alcohol is a highly effective general use cleaning solvent used to clean a variety of substrates and remove a variety of soils. Safe on plastics

Search
[00Z1420 at newark.com](#)

Electro- Wash PX Degreaser



Electro-Wash® PX is a fast drying, one step precision cleaning and degreasing agent safe for most plastics. Removes oils and hydraulic fluids from mechanical assemblies

Search
[00Z1138 at newark.com](#)

Pre- Saturated Isopropyl Alcohol Wipes



Low-linting wipes are pre-saturated with 70% pure IPA. Made of non-woven polyester. It is ideal for surface cleaning, stencil and tool cleaning and PCB cleaning

Search
[20T7267 at newark.com](#)

G3 Blue Shower Cleaner/ Degreaser



Non-flammable & powerful cleaner. Non-flammable. Non-ozone depleting. Safe on electronics. Rapid evaporation

Search
[81C8423 at newark.com](#)

G3 Flux Remover



G3 has a powerful spray and strong solvent that blasts off residues and cleans areas under components that a brush cannot touch

Search
[81C8424 at newark.com](#)

RTV 108 RTV Silicone Adhesive Sealant



One-component, ready-to-use adhesive sealant that cures to a tough, durable, resilient silicone rubber on exposure to atmospheric moisture at room temperature

Search
[00Z660 at newark.com](#)

Non- corrosive Silicone Adhesive Sealant



Thixotropic paste consistency and excellent corrosion-free adhesion to metals, including copper, plastics, ceramics, glass without the use of primers.

Search
[50B9935 at newark.com](#)

TSE397-C 100G Adhesive Sealant Tube



Excellent for thin section potting, filling small surface voids, self leveling and protective coating. Non-corrosive (MIL-A-46146A) to electronic metals, including copper and brass.

Search
[21J9764 at newark.com](#)

One-compo- nent, Ready- to-use High Strength Silicone Rubber Adhesive Sealant



RTV159 silicone rubber adhesive sealants generally help our customers in the aerospace and aviation industries ensure the integrity of their airframes and cabins.

Search
[00Z650 at newark.com](#)

3M NOVEC™ Flux Remover, 12 oz



Novec™ Flux Remover uses advanced 3M solvent technology to remove a wide variety of solder fluxes used in electronics manufacturing and repair. Evaporates quickly and leaves no residue

Search
[47Y8491 at newark.com](#)

262™ Threadlocker Medium-to- high-strength Adhesive



Industrial, maintenance & repair where medium to high strength thread-locking is needed

Search
[00Z1034 at newark.com](#)

TOOLS & PRODUCTION SUPPLIES


Flashforge Creator 3 Professional Independent Dual Extruder 3d Printer



Flashforge Creator 3 3D printer is capable of printing complex engineering-grade 3D prints. Creator 3 is the advanced version of the popular Creator Pro geared towards professionals

Search
[29AH0895](#) at [newark.com](#)

Flashforge Creator Pro Dual Extruder 3d Printer



Dual extrusion 3D printer, a heated build plate, and a fully enclosed build chamber allow for multi-material printing of temperature-sensitive materials.

Search
[29AH0917](#) at [newark.com](#)

Flash- Forge Inventor II 3D Printer



The Inventor II 3D Printer features Fused Filament Fabrication (FFF) printing technology, a build volume of 5.9 x 5.5 x 5.5", and a layer resolution of 50-400 microns. Equipped with a single extruder nozzle

Search
[29AH1053](#) at [newark.com](#)

Flashforge Guider 2s Professional 3d Printer With New High- Temperature Extruder



Guider 2S industrial grade 3D printer features built-in HD camera for remote monitoring, a massive build volume with the top level of FFF technology, designed to provide the maximum stability & ruggedness

Search
[29AH1005](#) at [newark.com](#)

Ultimaker S5 Dual Extrusion 3D Printer



Discover the easy-to-use desktop 3D printer with a large build volume that delivers accurate, industrial-grade parts. Simple setup with reliable dual extrusion, Ultimaker S5 is the complete 3D printing solution

Search
[58AC0293](#) at [newark.com](#)

Ultimaker S3 Dual Extrusion 3D Printer



S3 dual-extrusion 3D printer delivers high-quality, composites-capable performance in a smaller printer format. Ultimaker S3 brings all the great features of the Ultimaker S5

Search
[39AH1033](#) at [newark.com](#)

M3-ID 3D Printer with Dual Extruders



With industrial-grade precision and reliability in a machine compact enough to sit on your desk, the M3-ID is built for prototyping & production of precision parts

Search
[62AC0403](#) at [newark.com](#)

Ultimaker Green PLA 3mm Filament



Ultimaker 3mm Green PLA Filament Ensure the best possible prints by using the highest quality filament from Ultimaker

Search
[84Y8311](#) at [newark.com](#)

Ultimaker Transparent CPE 3mm Filament



CPE (co-polyester) materials are chemical resistant, tough, and demonstrate good dimensional stability. It is a preferred choice for both functional prototypes and mechanical parts

Search
[84Y8321](#) at [newark.com](#)

Ultimaker White ABS 3mm Filament



Ultimaker 3mm White ABS Filament Ensure the best possible prints by using the highest quality filament from Ultimaker

Search
[84Y8327](#) at [newark.com](#)

PVA 3D Printer Filament 750g



PVA (polyvinyl alcohol) is a water soluble support material for multiextrusion 3D printing. Ultimaker PVA is ideal for printing complex models that require supports for large overhangs

Search
[31AC4946](#) at [newark.com](#)

3D Printer Filament, 1.75mm, PLA, Blue



PLA (Polylactic Acid) filament for use with 3D printers, degradable bioplastic derived from plants. The 55252 from Verbatim is a blue colour, 1.75mm diameter PLA 3D filament.

Search
[44AC4192](#) at [newark.com](#)


3D Printer Filament, 1.75mm, ABS, Black



ABS (acrylonitrile butadiene styrene), copolymer blend of styrene, acryl and butadiene. The 55000 from Verbatim is a black colour, 1.75mm diameter ABS 3D filament

Search
[44AC4181](#) at [newark.com](#)

3D Printer Filament, PLA, Wood Effect, 1.75 mm Diameter



Wood / PLA blended Filament 1.75 mm diameter, Wood effectt, 185°C to 230°C (365°F-464°F) Compatible with all fused-filament 3D printers models

Search
[54AC6204](#) at [newark.com](#)

Premium 3D Printer Filament – PLA



The optimal choice for use in homes, schools, and hobbyists. A heated print bed is not required and when properly utilized, faster print speeds and lower layer heights can be achieved

Search
[07AH4513](#) at [newark.com](#)

TOOLS & PRODUCTION SUPPLIES

multicomp PRO 5-In-1 Multi-Tool Cutter /Stripper



Cuts and strips 10-22 AWG wire, crimps both insulated and non-insulated terminals, shears bolts



Search
[33AH6360 at newark.com](#)

multicomp PRO Heavy Duty Stripper/Crimper



Precision machined heavy-duty 8-22 AWG stripper, cutter and crimper



Search
[33AH6217 at newark.com](#)

multicomp PRO Solid and Stranded Wire Stripper



Strips and cuts 10 - 20 AWG Solid and Stranded wire.



Search
[33AH6218 at newark.com](#)

multicomp PRO Solid and Stranded Wire Stripper



Strips and cuts 32 - 22 AWG Solid and Stranded wire.



Search
[33AH6219 at newark.com](#)

multicomp PRO Compact Wire Stripper / Cutter



Strips and cuts 10 - 20 AWG Solid and Stranded wire.



Search
[33AH6220 at newark.com](#)

multicomp PRO 11-in-1 Multi-bit Screwdriver



Screwdriver includes the 8 bits and 3 nut drivers.



Search
[34AH5383 at newark.com](#)

multicomp PRO 10-in-1 Multi-bit Screwdriver



Screwdriver includes the 8 bits and 2 nut drivers.



Search
[34AH5384 at newark.com](#)

multicomp PRO 6-in-1 Multi-bit Screwdriver



Screwdriver includes the 4 bits and 2 nut drivers.



Search
[34AH5385 at newark.com](#)

multicomp PRO 5-in-1 Multi-bit Screwdriver



Screwdriver includes the 4 bits and 1 nut drivers.



Search
[34AH5386 at newark.com](#)

multicomp PRO 32PC Bit Block Multi driver - STANDARD BITS



Magnetic Tip Multi-bit screwdriver with 32PC bit block



Search
[34AH5387 at newark.com](#)

multicomp PRO 32PC Bit Block Multi driver - TAMPER BITS



Magnetic Tip Multi-bit screwdriver with Tamper proof bit block



Search
[34AH5388 at newark.com](#)

multicomp PRO 12-in-1 Precision Screwdriver



Features: Philips #00, #0, #1, Slotted 2mm, 3mm, 3.5mm, TORX® T5, T6, T7, T8, T10, T15



Search
[34AH5389 at newark.com](#)

DURATOOL 42-Piece Tool Kit



Perfect for small jobs at home or working on a small work project.



Search
[25AC4952 at newark.com](#)

DURATOOL 18" Black Weather- proof Case



Features 3-PC Foam with customizable center layer



Search
[76X0326 at newark.com](#)

DURATOOL 10.5" Yellow Weath- erproof Case



Features 3-PC Foam with customizable center layer



Search
[83X6732 at newark.com](#)

TEST EQUIPMENT

DAQ973 Data Acquisition System



- 3-slot mainframe with built-in 6½ digit DMM
- Basic 0.003% DCV accuracy
- Nine different switch, RF and control plug-in modules, including a new 4-channel simultaneous sampling digitizer available
- Up to 450 channel/s scan rate
- Up to 120 channels per system
- Up to one million points scanning memory
- Measures and converts 12 different input signals: Temperature with thermocouple, RTDs and thermistor; AC/DC volts and current; 2- and 4-wire resistance; frequency and period; Capacitance
- LAN, USB and GPIB connectivity
- Code compatible with the 34970A/34972A
- USB flash drive support to copy/log data in standalon applications
- BenchVue™ DAQ with enhanced time/frequency domain measurement included

Search

52AH3548 at newark.com

DAQ970A Data Acquisition System



3-Slot mainframe DAQ provides all of the same features as the DAQ973 above, excluding GPIB connectivity

Search

72AC4094 at newark.com

DAQ397A 4CH Simultaneous Sampling Digitizer



Digitizer module is capable of providing four simultaneously sampled channels which may be configured as a differential or a single-ended input. Each provides 4mA to power external IEPE transducers

Search

52AH3548 at newark.com

DAQM909A 20CH Solid State Multiplexer Module



This module is divided into two banks of 10 two-wire channels. All 20 channels switch both HI and LO inputs, thus providing fully isolated inputs to the internal DMM or an external instrument

Search

72AC4091 at newark.com

DAQM901A 20CH Armature Multiplexer Module



Versatile multiplexer for general purpose scanning combines dense, multifunction switching with 80-channel/second scan rates to address a broad spectrum of data acquisition applications

Search

72AC4092 at newark.com

DAQM903A 20CH Actuator/General Purpose Module



General purpose switch module has 20 independent SPDT relays. Use to cycle power to products under test, control indicator and status lights, or to actuate external power relays and solenoids

Search

74AC7828 at newark.com

DAQM907A Multifunction Digital + Analog Module



Module combines two 8-bit ports of digital I/O, 100KHz gated totalizer, and two ±12V or ±24mA analog outputs – all on a single earth-referenced module

Search

74AC7831 at newark.com

TEST EQUIPMENT

RTB Series 4CH 300MHz MSO/MDO Oscilloscope



300MHz 4CH Scope includes the 16CH MSO upgrade, Arbitrary waveform generator, I2C, SPI, UART/RS-232/RS-422/RS-485, CAN/LIN serial triggering and decode, Bode plot frequency response analysis

Search
[08AC3745 at newark.com](#)

FPC Series Bench 3GHz Spectrum Analyzer



This unit includes the following factory installed options: FPC-B22 Preamplifier, FPC-K7 Modulation analysis, FPC-K43 Receiver mode, FPC-K55 Advanced measurements

Search
[99AC0287 at newark.com](#)

FPC Series Bench 3GHz Spectrum Analyzer



This unit includes the following factory installed options: FPC-B22 Preamplifier, FPC-K7 Modulation analysis, FPC-K42 Vector reflection measurement, FPC-K43 Receiver mode, FPC-K55 Advanced measurements

Search
[99AC0288 at newark.com](#)

HMC8015 Two Channel Power Analyzer



AC/DC load and stand-by current characterization tester that enables measurements without additional tools such as a computer or remote infrastructure

Search
[99AC0303 at newark.com](#)

HMP4040 Four Channel 384W Power Supply



Isolated floating outputs feature overload and short-circuit protection and can be connected in series or parallel to obtain higher voltages or currents. Maximum voltage 128V, maximum current 40A

Search
[50AC9964 at newark.com](#)

NGE100 Series Three Channel Power Supply



Complete package includes NGE103B Supply, NGE-K101 Ethernet Remote Control, NGE-K102 Wireless LAN Remote Control, NGE-K103 Digital Trigger I/O

Search
[99AC0426 at newark.com](#)

NGL200 Series Two Channel Power Supply



The NGL202 delivers 60W per channel. Floating galvanically isolated outputs offer two-quadrant architecture allows it to function both as a source and a sink to simulate batteries and loads

Search
[99AC0427 at newark.com](#)

RTA Series Four Channel 1GHz MSO/MDO Oscilloscope



1GHz oscilloscope includes the following factory installed options; RTA-B1 mixed signal option, RTA-B6 ARB Generator, RTA-PK1US Application Bundle

Search
[99AC0518 at newark.com](#)

RTC Series Two Channel 300MHz MSO/MDO Oscilloscope



300MHz oscilloscope includes the following factory installed options: RTC-B1 mixed signal, RTC-K1, 2 and 3 (I2C/SPI, UART/RS232 and CAN/LIN trigger and decode and RTB-B6 ARB generator

Search
[99AC0519 at newark.com](#)

RTH Series Four Channel 500MHz Handheld Oscilloscope



Handheld oscilloscope includes RTH-B1 Mixed-Signal Option, RTH-K1 I2C/SPI, RTH-K2 UART/RS232, RTH-K3 CAN/LIN, RTH-K9 CAN-FD and RTH-K10 SENT trigger and decode options, RTH-K18 spectrum analysis

Search
[99AC0520 at newark.com](#)

RTM Series Four Channel 1GHz MSO/MDO Oscilloscope



Oscilloscope includes 16CH MSO upgrade, Arbitrary waveform generator, serial triggering and decode, Power analysis, Bode plot frequency response analysis, History and segmented memory upgrade

Search
[99AC0521 at newark.com](#)

FPH Series 4GHz Spectrum Analyzer



4GHz spectrum analyzer features numerous options including FPH-B22 Preamplifier, FPH-K15 Interference Analysis, FPH-K16 Signal Strength Mapping Measurement, FPH-K7 Modulation Analysis

Search
[40AH2356 at newark.com](#)

NGM Series Two Channel Power Supply



Powerful compact bench supply includes the following options: NGM-K102 wireless LAN remote control, NGM-K103 digital trigger I/O, NGM-K104 digital voltmeter functionality, NGM-K106 battery simulation

Search
[40AH2473 at newark.com](#)

RTE Series Four Channel 2GHz MSO/MDO Oscilloscope



Powerful benchtop instrument includes the following options: RTE-B1 Mixed Signal 400MHz, 16 channels, RTE-TDBNDL trigger and decode bundle, RTE-K18 multi-channel spectrum analysis

Search
[40AH2479 at newark.com](#)

SMC Series 3.2GHz Signal Generator



Compact and powerful signal generator covers 9KHz to 3.2GHz with +17dBm or better (typical) output power. AM, FM, M and pulse modulation are built in. Also includes SMC-B1 reference oscillator option

Search
[13AC0776 at newark.com](#)

TEST EQUIPMENT

MDO32 3-BW-1000 Oscilloscope




Two FlexChannel inputs, large 11.6" color touchscreen display with very small footprint.

Search
[02AH4124 at newark.com](#)

MDO34 3-BW-500 Oscilloscope




Four FlexChannel inputs, large 11.6" color touchscreen display with very small footprint.

Search
[02AH4132 at newark.com](#)

MDO34 3-BW-1000 Oscilloscope




Four FlexChannel inputs, large 11.6" color touchscreen display with very small footprint.

Search
[02AH4129 at newark.com](#)

MSO44 4-BW-1000 Oscilloscope




Four FlexChannel inputs, large 13.3" color touchscreen display, bandwidth upgradable to 1.5GHz

Search
[02AH4133 at newark.com](#)

MSO46 4-BW-500 Oscilloscope




Six FlexChannel inputs, large 13.3" color touchscreen display, bandwidth upgradable to 1.5GHz

Search
[02AH4142 at newark.com](#)

MSO46 4-BW-100 Oscilloscope




Six FlexChannel inputs, large 13.3" color touchscreen display, bandwidth upgradable to 1.5GHz

Search
[02AH4138 at newark.com](#)

MSO56 5-BW-1000 Oscilloscope




Six FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 2GHz

Search
[17AC9289 at newark.com](#)

MSO56 5-BW-2000 Oscilloscope




Six FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 2GHz

Search
[17AC9290 at newark.com](#)

MSO58 5-BW-1000 Oscilloscope




Eight FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 2GHz

Search
[17AC9297 at newark.com](#)

MSO58 5-BW-2000 Oscilloscope




Eight FlexChannel inputs, large 15.6" color touchscreen display.

Search
[17AC9298 at newark.com](#)

MSO58LP 1GHz PC / USB Oscil- loscope




Low profile mixed signal oscilloscope features eight FlexChannel inputs. DisplayPort and DVI-D video outputs support HD (1920 x 1080) resolution

Search
[56AC3039 at newark.com](#)

MSO64 6-BW- 1000 Four Channel 1GHz MSO/ MDO Oscilloscope




Four FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 8GHz

Search
[67AC9624 at newark.com](#)

MSO64 6-BW-2500 Four Chan- nel 2.5GHz MSO/MDO Oscilloscope




Four FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 8GHz

Search
[67AC9625 at newark.com](#)

MSO64 6-BW-4000 Four Chan- nel 4GHz MSO/MDO Oscilloscope




Four FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 8GHz

Search
[67AC9626 at newark.com](#)

MSO64 6-BW-6000 Four Chan- nel 6GHz MSO/MDO Oscilloscope




Four FlexChannel inputs, large 15.6" color touchscreen display, bandwidth upgradable to 8GHz

Search
[67AC9627 at newark.com](#)

TEST EQUIPMENT

2470 Source Meter



The 2470 High Voltage SourceMeter® Source Measure Unit (SMU) instrument makes testing intuitive with minimized learning curve. Wide coverage up to 1100VDC/1A, 20W max, 10 fA measure resolution

Search
[02AH4148](#) at [newark.com](#)

2602B Source Meter



Series 2600B SourceMeter SMU Instruments – 2602B combines a power supply, true current source, 6½-digit DMM, arbitrary waveform generator, pulse generator & electronic load, in a single unit.

Search
[44W8034](#) at [newark.com](#)

2450 Source Meter



Model 2450 features an innovative graphical user interface (GUI) and advanced, capacitive touchscreen for intuitive use and minimized learning curve. It is well-suited for characterizing semi-conductors & more

Search
[88W3815](#) at [newark.com](#)

2410 Source Meter



Designed for test applications demanding tightly coupled sourcing and measurement. Provides voltage and current sourcing as well as measurement capabilities. 1,100V, 1A, 20W.

Search
[19K4451](#) at [newark.com](#)

2401 Source Meter



Designed for test applications demanding tightly coupled sourcing and measurement. Provides voltage and current sourcing as well as measurement capabilities. 20V, 1A, 20W.

Search
[64T2777](#) at [newark.com](#)

2400 Source Meter



Designed for test applications demanding tightly coupled sourcing and measurement. Provides voltage and current sourcing as well as measurement capabilities. 200V, 1A, 20W.

Search
[41J2103](#) at [newark.com](#)

DMM7510 Digital Bench Multimeter



Combines the benefits of a precision DMM, a graphical touchscreen display, and high resolution digitizer to create a graphical sampling multimeter. The digitizer provides unprecedented signal analysis.

Search
[29Y2096](#) at [newark.com](#)

DMM6500 Digital Bench Multimeter



Large 5 capacitive touch screen provides “pinch and zoom” simplicity. 15 measurement functions include capacitance, temperature, and digitizing. Expanded measurement ranges and stores up to 7M readings

Search
[51AC7032](#) at [newark.com](#)

DAQ6510 Data Acquisition Unit



Precision data acquisition and logging system creates a new level of simplicity compared with the often complicated configuration and control found in many stand-alone solutions. 12 different control modules

Search
[51AC7225](#) at [newark.com](#)

RS232 Interface for DAQ6510



RS232 option provides serial control of unit as well as datalogging

Search
[56AC3032](#) at [newark.com](#)

GPIB Interface for DAQ6510



Standard GPIB bus interface provides external control of unit as well as datalogging

Search
[56AC3031](#) at [newark.com](#)

2601B System Source Meter



Tightly integrated, 4-quadrant voltage/current source and measure instruments offer best in class performance with 6½-digit resolution. Dual Channel 3A DC, 10A pulse

Search
[44W8033](#) at [newark.com](#)

2604B System Source Meter



Tightly integrated, 4-quadrant voltage/current source and measure instruments offer best in class performance with 6½-digit resolution. Dual Channel 3A DC, 10A pulse

Search
[44W8035](#) at [newark.com](#)

2611B System Source Meter



Tightly integrated, 4-quadrant voltage/current source and measure instruments offer best in class performance with 6½-digit resolution. Single Channel 200V, 10A pulse

Search
[44W8036](#) at [newark.com](#)

2612B System Source Meter



Tightly integrated, 4-quadrant voltage/current source and measure instruments offer best in class performance with 6½-digit resolution. Dual Channel 200V, 10A pulse

Search
[44W8037](#) at [newark.com](#)

TEST EQUIPMENT

TG267 Thermal Camera



Handheld thermal camera reduces diagnostic time while simplifying reporting & long-term monitoring of equipment & systems throughout a facility. 160x120 IR pixel imager, -25° to +380°F temperature range

Search

[40AH1830](#) at [newark.com](#)

TG297 Thermal Camera



Handheld thermal camera combines accurate measurement with the ability to image temperatures as high as 1030°C (1886°F). 160x120 IR pixel imager, 30:1 distance to spot ratio

Search

[40AH1831](#) at [newark.com](#)

ETS320 Stationary Thermal Inspection Camera



Engineered specifically for lab electronics testing, unit is battery-powered and hands-free. USB connectivity allows immediate analysis and sharing of thermal data. 320 x 240 IR resolution, 45° x 34° field of view

Search

[14AC2256](#) at [newark.com](#)

Flir One Pro LT Pro Smart-phone IR Camera




IR Camera Attachment for IOS Smartphones - 80 x 60 IR Resolution

Search

[82AC9755](#) at [newark.com](#)

Flir One Pro LT Pro Smart-phone IR Camera



IR Camera Attachment for Smartphones with Micro USB - 80 x 60 IR Resolution

Search

[82AC9756](#) at [newark.com](#)

Flir One Pro LT Pro Smart-phone IR Camera



IR Camera Attachment for Smartphones with USB-C - 80 x 60 IR Resolution

Search

[82AC9757](#) at [newark.com](#)

C2 Pocket Thermal Imaging Camera



Pocket Thermal Imager with 80 x 60 IR Resolution

Search

[41Y9214](#) at [newark.com](#)

E95-24 Thermal Imaging Camera



Handheld IR Camera with 464 x 348 IR Resolution and 17mm Lens

Search

[12AC7159](#) at [newark.com](#)

E8-XT WIFI Thermal Imaging Camera



Handheld IR Camera with 320 x 240 IR Resolution and WiFi Connectivity

Search

[99AC7471](#) at [newark.com](#)

Powerful Pocket-sized Thermal Camera



Features a 3" touchscreen display, 80 x 60 resolution, 41° x 31° field of view and WiFi connectivity. In stock at Newark

Search

[11AC9780](#) at [newark.com](#)

TiX501 Thermal Imaging Camera



Handheld Thermal Imager with 640 x 480 Resolution, WiFi, and 5.7" Touchscreen Display

Search

[01AH3577](#) at [newark.com](#)

Ti-401 Pro Thermal Imaging Camera




Handheld Thermal Imager with 640 x 480 Resolution, WiFi, and 3.5" Touchscreen Display

Search

[01AH3578](#) at [newark.com](#)

PTi120 Pocket Thermal Imaging Camera



Pocket Thermal Imager with 120 x 90 IR Resolution

Search

[01AH3576](#) at [newark.com](#)

FLK-TiS60+ 30Hz Thermal Imager



Provides 320 x 240 resolution with 34° x 26° field of view. IR-Fusion™ technology allows you to see things that are otherwise invisible to reveal problems that are otherwise undetectable

Search

[42AH0127](#) at [newark.com](#)

FLK-TiS20+ 9Hz Thermal Imager



Compact thermal imager provides 120 x 90 resolution with 50° x 38° field of view. IP54 rated, 2M drop tested, longest battery life of all Fluke Thermal Imagers

Search

[42AH0126](#) at [newark.com](#)

TEST EQUIPMENT

MDA-550 Four Channel Motor Drive Analyzer

FLUKE


Locate and troubleshoot typical problems on inverter type motor-drive systems. Measure key motor-drive parameters including voltage, current, DC Bus voltage level and AC ripple, voltage and more

Search

[73AC9474 at newark.com](#)

435-II 3-Phase Power Quality and Energy

FLUKE


Locate and troubleshoot power quality problems in single and three-phase power distribution systems. Measure and quantify energy losses due to harmonics and unbalance issues

Search

[76T4892 at newark.com](#)

VR1710 Voltage Quality Recorder

FLUKE


Single-phase recorder is an easy-to-use solution for detecting and recording voltage quality problems. Parameters including RMS average, transients, flicker, and harmonics are recorded

Search

[71M3716 at newark.com](#)

87V Industrial Digital Multimeter

FLUKE


The gold standard in handheld digital instrumentation, the Fluke 87V troubleshoots issues on motor drives, in plant automation, power distribution, and electromechanical equipment

Search

[96H6287 at newark.com](#)

87V-E2 Industrial Digital Multimeter Kit

FLUKE


Kit includes the Fluke 87V meter, TL75 test leads, AC72 alligator clips, temperature probe, heat resistant test leads, removable test probes, long reach alligator clips, magnetic holder, carrying case

Search

[12M6081 at newark.com](#)

87V-MAX Heavy Duty Industrial Digital Multimeter

FLUKE


New ruggedized version of the popular Fluke 87V, this meter provides extended operating temperature range, IP67 rating and is drop tested to four meters

Search

[40AH0535 at newark.com](#)

Model 289 Industrial True-RMS Multimeter

FLUKE


Datalogging meter solves complex problems in plant automation, power distribution, and electronics. Log data and review graphically on-screen to quickly solve problems and minimize downtime

Search

[42M9905 at newark.com](#)

Model 179-ESFP Digital Multimeter

FLUKE


True RMS Digital Multimeter is the preferred solution for professional technicians around the world. Measure AC/DC voltage and current, capacitance, frequency, resistance and temperature

Search

[25C4804 at newark.com](#)

Model 179-EDA2 Electronics Combo Multimeter Kit

FLUKE


Kit includes the Fluke 179 multimeter, TL910 electronic test probes, 80BK-A integrated temperature probe, TPAK magnetic hanger, AC280 SureGrip hook clips, TL224 SureGrip insulated test leads & case

Search

[31M7868 at newark.com](#)

Model 117 Digital Multimeter

FLUKE


The ideal meter for demanding settings like commercial buildings, hospitals and schools. True-RMS meter measures AC/DC volts and amps, resistance, frequency and capacitance. CAT III 600 V safety rated

Search

[83K1721 at newark.com](#)

Model 115 Digital Multimeter

FLUKE


True RMS digital multimeter is the answer for general purpose electrical and electronic test requirements. Measure AC/DC current and voltage, capacitance, frequency and resistance plus continuity & diode check

Search

[83K1718 at newark.com](#)

Model 175-ESFP Digital Multimeter

FLUKE


True-RMS digital multimeter provides baseline features needed for troubleshooting and repairing electrical and electronic systems. Delivers accurate true-RMS AC current and voltage and more

Search

[25C4796 at newark.com](#)

5674C Deluxe Electronic Test Probe Set

Panasonic Electronics


Perfect for any DMM, this complete kit includes six test leads, two test probes, two alligator clips, one test clip, four probe adapters and carry pouch

Search

[73K9941 at newark.com](#)

5325A DMM Test Probe Kit

Panasonic Electronics


Perfect for any DMM, this kit includes the 5309A test probe set, 6262 slide-on extended tip set and 6264 alligator adapter set

Search

[94F1526 at newark.com](#)

6730 Four-Wire Kelvin Test Lead Set

Panasonic Electronics


Test lead set is designed for use with any device equipped with four-wire Kelvin test lead inputs. Overall length is 46" with wide jaw alligator clips that open to 0.8"

Search

[66H6600 at newark.com](#)

TEST EQUIPMENT

2206B Two Channel 50MHz USB Oscil- loscope



Powerful and compact PC based 50MHz two-channel oscilloscope also functions as a spectrum analyzer, function generator, arbitrary waveform generator, serial bus analyzer and logic analyzer

Search

[81Y4874](#) at [newark.com](#)

3406D Four Channel 200MHz USB Oscil- loscope



Powerful USB 3.0 based scope features four channels, 200MHz bandwidth 1 GS/s real-time sampling rate, fast waveform updates and built-in arbitrary waveform generator

Search

[39Y8658](#) at [newark.com](#)

3406D Four Channel 200MHz USB MSO Oscillo- scope



Powerful USB 3.0 based scope features four analog and 16 digital channels, 200MHz bandwidth 1 GS/s real-time sampling rate, fast waveform updates and built-in arbitrary waveform generator

Search

[85X3586](#) at [newark.com](#)

4824 Eight Chan- nel USB Oscillo- scope



USB based 20MHz oscilloscope features eight analog channels allowing you to easily analyze audio, vibration, power, and timing of complex systems, and perform a wide range of precision measurements

Search

[38X6261](#) at [newark.com](#)

5244D Two Channel 200MHz USB Oscil- loscope



Two channel 200MHz USB oscilloscope features FlexRes® 8 to 16 bit hardware resolution. Perfect for design, research, education and service. Also features up to 512MS capture memory, 130,000 wfps

Search

[65AC5474](#) at [newark.com](#)

5244D MSO Two Channel 200MHz USB Oscilloscope



Two channel 200MHz USB oscilloscope provides all of the features of the Model 5244D, plus 16 digital channels

Search

[67AC4738](#) at [newark.com](#)

5444D Four Channel 200MHz USB Oscil- loscope



Four channel 200MHz USB oscilloscope features FlexRes® 8 to 16 bit hardware resolution. Perfect for design, research, education and service. Also features up to 512MS capture memory, 130,000 wfps

Search

[67AC4742](#) at [newark.com](#)

5444D MSO Four Channel 200MHz USB Oscil- loscope



Four channel 200MHz USB oscilloscope provides all of the features of the Model 5444D, plus 16 digital channels

Search

[67AC4743](#) at [newark.com](#)

6404D Four Channel 500MHz USB Oscil- loscope



500MHz bandwidth plus real-time sampling rate of 5GS/s allow display of single-shot pulses with 200ps resolution. 50 GS/s sampling rate allows timing resolution for repetitive signals

Search

[08X2009](#) at [newark.com](#)

TA041



25MHz differential probe allows safe and accurate method of making high-voltage differential measurements. Differential voltage range (100:1): ±700 V (DC + peak AC) or 700 V RMS

Search

[02M0836](#) at [newark.com](#)

TA167



Clamp probe enables current measurements up to 2000A. Bandwidth is DC to 20KHz

Search

[18X2928](#) at [newark.com](#)

TA044



70MHz differential probe allows safe and accurate method of making high-voltage differential measurements. Differential voltage range (1000:1): ±7KV (DC + peak AC) or 700 V RMS

Search

[95M7351](#) at [newark.com](#)

TA058



50MHz differential probe allows safe and accurate method of making high-voltage differential measurements. Differential voltage range (100:1): ±700 V (DC + peak AC) or 700 V RMS

Search

[33P8250](#) at [newark.com](#)

TC-08 Thermo- couple Data Log- ger



USB powered data logger, a cost-effective temperature measurement solution. With eight direct thermocouple inputs, the USB TC-08 can take accurate, rapid readings. Records temperatures -270 °C to +1820 °C

Search

[02M0855](#) at [newark.com](#)

TC-08 Terminal Board



For use with the TC-08 logger, converts inputs to screw terminal type, allowing logger to be used to record a wide range of signals, ±5VDC, and 4~20mA

Search

[05AC0237](#) at [newark.com](#)

TEST EQUIPMENT

MDO-2102A 100MHz 2CH Oscilloscope

GW INSTEK


100MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5131 at newark.com](#)

MDO-2202A 200MHz 2CH Oscilloscope

GW INSTEK


200MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5133 at newark.com](#)

MDO-2302A 300MHz 2CH Oscilloscope

GW INSTEK


300MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5135 at newark.com](#)

MDO-2102AG 100MHz 2CH Oscilloscope with Function Generator

GW INSTEK


100MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5132 at newark.com](#)

MDO-2202AG 200MHz 2CH Oscilloscope with Function Generator

GW INSTEK


200MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5134 at newark.com](#)

MDO-2302AG 300MHz 2CH Oscilloscope with Function Generator

GW INSTEK


300MHz mixed domain oscilloscope features a 2GSa/s Max sampling rate and memory depth of 20M/CH. It's also a dual-domain test platform that includes a spectrum analyzer measurement mode

[Search](#)
[51AH5136 at newark.com](#)

PEL-3021H DC Electronic Load - 175W

GW INSTEK


Single channel high speed programmable load for testing large scale computer and server power supplies. Up to five units may be cascaded for increased capacity - half rack mount

[Search](#)
[28AH0423 at newark.com](#)

4062B 40MHz Dual Channel Function/ ARB Waveform Generator

DE PRECISION


Capable of producing precise sine, square, triangle, pulse, and arbitrary waveforms. Dual architecture design allow toggling between DDS and true point-by-point arbitrary modes

[Search](#)
[51AH4560 at newark.com](#)

4063B 80MHz Dual Channel Function/ ARB Waveform Generator

DE PRECISION


Capable of producing precise sine, square, triangle, pulse, and arbitrary waveforms. Dual architecture design allow toggling between DDS and true point-by-point arbitrary modes

[Search](#)
[51AH4561 at newark.com](#)

4064B 120MHz Dual Channel Function/ ARB Waveform

DE PRECISION


Capable of producing precise sine, square, triangle, pulse, and arbitrary waveforms. Dual architecture design allow toggling between DDS and true point-by-point arbitrary modes

[Search](#)
[51AH4562 at newark.com](#)

8514B 1,500W DC Electronic Load



Versatile tool is ideal for evaluating DC power supplies, DC-DC converters, batteries, battery chargers, and photovoltaic arrays

[Search](#)
[40AH1291 at newark.com](#)

8542B 150W DC Electronic Load



Versatile tool is ideal for evaluating DC power supplies, DC-DC converters, batteries, battery chargers, and photovoltaic arrays

[Search](#)
[07AH3449 at newark.com](#)

8510B 600W DC Electronic Load



Versatile tool is ideal for evaluating DC power supplies, DC-DC converters, batteries, battery chargers, and photovoltaic arrays

[Search](#)
[07AH3448 at newark.com](#)

8502B 300W DC Electronic Load



Versatile tool is ideal for evaluating DC power supplies, DC-DC converters, batteries, battery chargers, and photovoltaic arrays

[Search](#)
[07AH3447 at newark.com](#)

8500B 300W DC Electronic Load



Versatile tool is ideal for evaluating DC power supplies, DC-DC converters, batteries, battery chargers, and photovoltaic arrays

[Search](#)
[07AH3446 at newark.com](#)

TEST EQUIPMENT

multicomp^{PRO} Handheld DSO, 20MHZ  <p>20MHz, 8bit handheld digital storage oscilloscope with digital multimeter</p> <p>Search 10AH2397 at newark.com</p>	multicomp^{PRO} Handheld DSO, 60MHZ  <p>60MHz, 8bit handheld digital storage oscilloscope with digital multimeter</p> <p>Search 10AH2398 at newark.com</p>	multicomp^{PRO} Pc Oscilloscope, 25mhz, 2ch  <p>2 channel, 25MHz, 8bit PC-based oscilloscope. Featuring 5K record lengths, friendly UI, multi-trigger options</p> <p>Search 10AH2399 at newark.com</p>	multicomp^{PRO} Pc Oscilloscope, 25mhz, 2ch  <p>2 channel, 25MHz, 8bit PC-based oscilloscope with USB 2.0 isolation</p> <p>Search 10AH2400 at newark.com</p>	multicomp^{PRO} Pc Oscilloscope, 60mhz, 2ch  <p>2 channel, 60MHz, 8bit PC-based oscilloscope. Featuring 10M record lengths, friendly UI, multi-trigger options</p> <p>Search 10AH2401 at newark.com</p>
multicomp^{PRO} Pc Oscilloscope, 100mhz, 2ch  <p>2 channel, 100MHz, 8bit PC-based oscilloscope. Featuring 10M record lengths, friendly UI, multi-trigger options</p> <p>Search 10AH2402 at newark.com</p>	multicomp^{PRO} Mixed Signal Oscilloscope, 100MHZ  <p>2-in-1, 8bit, 100MHz mixed signal oscilloscope with logic analyser</p> <p>Search 10AH2396 at newark.com</p>	multicomp^{PRO} Digital Storage Oscilloscope, 20mhz  <p>2 channel, 20MHz, 8bit, digital oscilloscope. 7" display</p> <p>Search 10AH2392 at newark.com</p>	multicomp^{PRO} Digital Storage Oscilloscope, 50mhz  <p>2 channel, 50MHz, 8bit, digital oscilloscope. 7" display</p> <p>Search 10AH2393 at newark.com</p>	multicomp^{PRO} Digital Storage Oscilloscope, 100mhz  <p>2 channel, 100MHz, 8bit, digital oscilloscope. 7" display</p> <p>Search 10AH2394 at newark.com</p>
multicomp^{PRO} Digital Storage Oscilloscope, 100mhz  <p>2 channel (1 external), 100MHz, 8bit, digital storage oscilloscope. 8" display</p> <p>Search 10AH2395 at newark.com</p>	multicomp^{PRO} Digital Storage Oscilloscope, 100mhz  <p>2 Channel 100MHz, 12bit, digital oscilloscope, 8" display</p> <p>Search 10AH2403 at newark.com</p>	multicomp^{PRO} Digital Storage Oscilloscope, 100mhz  <p>4 Channel 100MHz, 8bit, digital oscilloscope, 8" display</p> <p>Search 10AH2404 at newark.com</p>	multicomp^{PRO} Spectrum Analyser, 1.5ghz  <p>Frequency range from 9KHz up to 1.5GHz, 9KHz up to 3.6GHz</p> <p>Search 10AH2390 at newark.com</p>	multicomp^{PRO} Spectrum Analyser, 3.6ghz  <p>Frequency range from 9KHz up to 3.6GHz</p> <p>Search 10AH2391 at newark.com</p>

TEST EQUIPMENT

multicomp^{PRO} Handheld DMM With Bluetooth  5/6 bit resolution handheld digital multimeter. with data logger Search 10AH2405 at newark.com	multicomp^{PRO} Bench Digital Multimeter  4.5 digit bench-type digital multimeter. 4" Display Search 10AH2406 at newark.com	multicomp^{PRO} Bench Digital Multimeter  5.5 digit bench-type digital multimeter. 4" Display Search 10AH2407 at newark.com	multicomp^{PRO} Bench Top emote Programmable Linear Mode Power Supply  Linear Mode Power Supply, 0.1V-18V DC, 0-6A, 3 Output Search 42AH0476 at newark.com	multicomp^{PRO} Bench Top Remote Programmable Linear Mode Power Supply  Linear Mode Power Supply, 0.1V - 32V DC, 0-3.5A, 3 Output Search 42AH0477 at newark.com
multicomp^{PRO} Switching Mode Power Supply  1-20V, 5A, 3 Output Search 42AH0478 at newark.com	multicomp^{PRO} Switching Mode Power Supply  1-36V 3A, 3 Output Search 42AH0479 at newark.com	multicomp^{PRO} Switching Mode Power Supply  1-60V, 1.6A, 3 Output Search 42AH0480 at newark.com	multicomp^{PRO} Auto-Ranging Power Supply  0.5-36V, 5A, 1 Output Search 42AH0481 at newark.com	multicomp^{PRO} Auto-Ranging Power Supply  0.5-36V, 5A (80W) 1 Output Search 42AH0482 at newark.com
multicomp^{PRO} DC Linear Power Supplies  150W, 0-30V, 0-5A Single-channel, linear Search 42AH0482 at newark.com	multicomp^{PRO} DC Linear Power Supplies  180W, 0-60V, 0-3A Single-channel, linear Search 42AH0484 at newark.com	multicomp^{PRO} Wide Range Programmable Power Supply  0-30V, 0-30A, 300W, wide range voltage with a single channel Search 42AH2836 at newark.com	multicomp^{PRO} Wide Range Programmable Power Supply  0-60V, 0-15A, 300W, wide range voltage with a single channel Search 42AH2837 at newark.com	multicomp^{PRO} DC Electric Load  300W, 0-120V, 0-30A, Single Channel Search 52AH6649 at newark.com

SOLDERING STATIONS & SUPPLIES

60W Soldering Station

TENMA


ESD safe thermo-control anti-static digital soldering station with LCD display

Search
[56T2208](#) at [newark.com](#)

Fume Extractor

TENMA


ESD safe solder fume extractor

Search
[37J0035](#) at [newark.com](#)

4-IN-1 Rework Station

multicomp PRO


4-in-1 rework station, including functionality for soldering, hot air, desoldering and electronic tweezers

Search
[72AC8885](#) at [newark.com](#)

60W Soldering Station

multicomp PRO


Digital Soldering Station, 60W, ESD Safe

Search
[39AH0163](#) at [newark.com](#)

80W Soldering Station

multicomp PRO


Digital Soldering Station, 80W, ESD Safe

Search
[39AH0164](#) at [newark.com](#)

100W Soldering Station

multicomp PRO


Digital soldering station, 100W, ESD SAFE

Search
[39AH0165](#) at [newark.com](#)

Temperature Controlled Soldering Iron

multicomp PRO


50W Adjustable & Constant Temperature Soldering Iron & Stand (ESD Safe)

Search
[39AH0166](#) at [newark.com](#)

USB Soldering Iron

multicomp PRO


USB Soldering Iron especially for precision soldering.

Search
[39AH0167](#) at [newark.com](#)

Soldering Iron, 80W

multicomp PRO


Portable, temperature-adjustable, high-temperature control soldering iron

Search
[39AH0168](#) at [newark.com](#)

Soldering Iron, 150W

multicomp PRO


Portable, temperature-adjustable, high-temperature control soldering iron

Search
[39AH0169](#) at [newark.com](#)

Fume Extractor

multicomp PRO


Desktop-type ESD Safe Fume & Solder Smoke Absorber

Search
[39AH0171](#) at [newark.com](#)

Soldering Iron, 80W

multicomp PRO


80W portable, temperature-adjustable, high-temperature control soldering iron.

Search
[39AH0172](#) at [newark.com](#)

Soldering Iron, 150W

multicomp PRO


150W portable, temperature-adjustable, high-temperature control soldering iron.

Search
[39AH0173](#) at [newark.com](#)

Multi-Functional Soldering System, 150W

multicomp PRO


150W Single Soldering Rework Stations

Search
[39AH0174](#) at [newark.com](#)
















Multi-Functional Soldering System, 200W

multicomp PRO


200W Dual Channel Soldering Rework Stations

Search
[39AH0175](#) at [newark.com](#)

SOLDERING & ESD SUPPLIES

<p>DURATOOL</p> <p>Tip Tinner</p>  <p>Tip Tinner, Lead Free, 0.5oz</p> <p>Search 10N694 at newark.com</p>	<p>multicomp</p> <p>Solder wire</p>  <p>96.1/2.6/0.3 Solder Wire, 1lb</p> <p>Search 35M4394 at newark.com</p>	<p>DURATOOL</p> <p>Solder wire</p>  <p>60/40 Solder wire with rosin activated (RA) flux, 1lb</p> <p>Search 20M4920 at newark.com</p>	<p>multicomp</p> <p>Silicone Thermal Dielectric Grease</p>  <p>Translucent, water repelling (hydrophobic), non-melting, and lubricating dielectric grease, 85 ml</p> <p>Search 71AC4521 at newark.com</p>	<p>multicomp</p> <p>Carbon Conductive Grease</p>  <p>Electrically conductive silicone grease for improving electrical connections</p> <p>Search 71AC4520 at newark.com</p>
<p>multicomp</p> <p>Breadboard</p>  <p>Solderless ABS Prototyping Board</p> <p>Search 99W1760 at newark.com</p>	<p>multicomp</p> <p>AirDuster</p>  <p>Air duster with compressed gas for energized equipments Non-flammable, non-ozone depleting</p> <p>Search 78H4044 at newark.com</p>	<p>multicomp</p> <p>Freeze Spray</p>  <p>10oz Diagnostic Freeze Spray</p> <p>Search 78H4045 at newark.com</p>	<p>multicomp</p> <p>Dissipative Mat</p>  <p>Dissipative Mat, 2 Layer, Rubber, Blue, 2ft W x 3ft L</p> <p>Search 27T3780 at newark.com</p>	<p>DURATOOL</p> <p>ESD Heel Grounder</p>  <p>Heel Grounder with conductive grounding tab</p> <p>Search 14N9048 at newark.com</p>
<p>multicomp</p> <p>Anti Static Wrist Strap</p>  <p>Wrist strap set with wristband and grounding cord</p> <p>Search 74M5598 at newark.com</p>	<p>DURATOOL</p> <p>ESD Field Service Kit</p>  <p>24" x 24" ESD Mat, Ground Snap & Cord, Wrist Band & Coiled Ground Cord</p> <p>Search 14N9060 at newark.com</p>	<p>DURATOOL</p> <p>ESD Snap Mounting Kit,</p>  <p>Universal Snap Kit with threaded backing washer</p> <p>Search 02P9686 at newark.com</p>	<p>DURATOOL</p> <p>ESD Vacuum Cleaner Set</p>  <p>Static-controlled Vacuum Cleaner with conductive construction to prevent damage to sensitive electronic components</p> <p>Search 18M9991 at newark.com</p>	<p>DURATOOL</p> <p>Magnifier Clamp Tool</p>  <p>Helping Hands Magnifier with a 4X magnification</p> <p>Search 47T9913 at newark.com</p>

PASSIVE COMPONENTS

NRC-AS Series Sulfur-resistant AEC-Q200 Chip Resistors



Ideal for for Harsh Environments. Suitable for high-reliability applications in challenging applications. Available in standard and high power ratings

Search
52AH2728 at newark.com

NTR Series Thin Film Resistors



Precise tolerance and temperature coefficient, eia standard case sizes (0201 ~ 2512) low noise, thin film (NiCr) construction, reflow solderable (Pb free termination finish)

Search
16AH3769 at newark.com

NPIS_LS Series Ultralow Profile Power Inductor, High Current & High Inductance



Resin shielded power inductor high current (up to 10.35 amps) and high inductance for use in DC/DC converters. Ultra-small (down to 2mm)

Search
41AH9080 at newark.com

Surface Mount MELF Resistor



Surface Mount MELF Resistor, 56 kohm, SMA-A Series, 350 V, Metal Film, 1 W, $\pm 1\%$

Search
73AC2516 at newark.com

SMD Chip Resistor



SMD Chip Resistor, 2512 [6432 Metric], 270 ohm, 3522 Series, 250 V, Thick Film, 3 W

Search
84Y5134 at newark.com

Panel Mount Resistor



Resistor, Solder Lug, 47 ohm, HSC Series, 150 W, $\pm 5\%$, Solder Lug, 2.5 kV

Search
51R8242 at newark.com

High Current SMD Jumpers



JR series of high current jumpers offers handling up to 100 amps (2512 size) with resistance values below 0.2 milli-ohms

Search
07AH3442 at newark.com

2000 Watt Planar Resistor



The TAP2000 is ideal for variable speed drives, power supplies, control devices, robotics, motor control and other power designs

Search
99AC8567 at newark.com

Resistive Force Sensor for Industrial Use



Typical force-sensing resistors are characterized for Human-Machine Interface (HMI) or Machine-Machine Interface (MMI) applications with a sensing range from circa 20g to 5Kg

Search
02AH9092 at newark.com

CRCW-HP Pulse Proof, High Power Thick Film Resistor



The CRCW-HP Thick Film Chip Resistors combine high power and pulse proof with double-sided resistive element, automotive qualified, 0402-2512 sizes, 1% and 5% tolerance, from 1 Ω thru 1M Ω and 0 Ω jumper

Search
68R2985 at newark.com

TNPW High Stability Thin Film Chip Resistor



The TNPW thin film resistor is an excellent choice where precision and long term stability is required, offering superior moisture resistance, automotive qualified, sulfur resistant, 0402-1210 sizes

Search
26R4218 at newark.com

MM_ series Thin Film MELF Resistors



The cylindrical construction of MMU0102, MMA0204 & MMB0207 MELF resistors offer reliability, stability & precision with more resistive area, optimal pulse performance, automotive qualified & sulfur resistant

Search
64K1889 at newark.com

AEC-Q200 Qualified CRCW-HP Thick-Film Chip Resistor



Offers engineers up to three times the rated power of standard thick film devices in the same package size, while providing outstanding pulse handling capability

Search
68R2980 at newark.com

Green High Voltage Chip Resistors



Completely free of Pb and its compounds, RoHS compliant without exemption featuring anti-sulphur construction with continuous voltages up to 3kV

Search
09AH9488 at newark.com

Green Thick-Film Chip Arrays



GBCN is the latest addition to our range of green thick-film resistor products. It is essentially a variant of BCN, designed using green thick film materials which are completely free of Pb (lead) and its compounds

Search
49AH7297 at newark.com

ANTENNAS, PASSIVES & SEMIS

UHF RFID Reader Antenna (ISM, LPWA)



Covers the 902 ~ 928 MHz frequency range for RFID, ISM and LPWA applications; Includes MMCX-JW RF connector for easy installation; Suitable for industrial automation and asset management designs

Search
[65AC5591 at newark.com](#)

External WiFi Antenna for Portable and Network



Covers the 2.4 GHz frequency range for WiFi and ISM applications; Compact size is ideal for flexibility in space-constrained designs; Whip type with connector mount for easy installation

Search
[65AC5575 at newark.com](#)

AMPM/AMJM Series MEMS for IIoT Designs



Optimized for low power consumption, including ultra-low power standby capability; Offers wide operating temperature range and shock/vibration resistance to enhance durability

Search
[67AC9577 at newark.com](#)

B82721K Series Radial Leaded Common Mode Chokes



High resonance frequency featuring a special winding technique. Ideal for suppression of common-mode interference and switch-mode power applications

Search
[19M9137 at newark.com](#)

Sealed Panel Control Rotary Potentiometers - 3310 Series



A rugged potentiometer in a compact package that saves board and panel space. Withstands typical industrial washing processes

Search
[33M2801 at newark.com](#)

Browse our large portfolio of 0402 to 2220 size MLCCs



Downsizing might be right for some applications, but others require larger sizes of MLCCs to keep the required electrical performance, volumetric capacitance and DC bias behavior

Search
[15AC9339 at newark.com](#)

ZMOD4410 Gas Sensor Module for TVOC & Indoor Air Quality



Provides the measurement of total organic compounds (TVOC) concentrations and indoor air quality (IAQ). The module algorithm also estimates carbon dioxide level (eCO2)

Search
[26AH6361 at newark.com](#)

175°C Rated Multilayer Varistor



Offer a small, SMT, TVS solution, requiring zero derating of transient current, power, or energy at high temperatures. They can replace large and derated TVS diodes being used in high temp applications

Search
[98AC5707 at newark.com](#)

High Reliability Supercapacitor



AVX High Reliability SCM series offer extended life of supercapacitors exposed to elevated temperatures and moisture levels

Search
[56AC6442 at newark.com](#)

COTS+ Tantalum Polymer



AVX TCS series of multianode Tantalum polymers are low ESR and high CV, but offer additional enhanced reliability for applications with long lifetimes

Search
[12AC2511 at newark.com](#)

High Temperature Tantalum Chip Capacitor with Extension to 200°C



AVX THJ series of 175°C and 200°C Tantalum chip capacitors offer extremely reliable, low ESR, and high CV capacitor solutions ideal for down hole and under hood applications

Search
[01X0123 at newark.com](#)

TMBS® Rectifiers in SMP Package



3 A rating is the industry's highest for the SMP package. Low forward voltage drops reduce power losses and improve efficiency. Available in eSMP® series low profile SMP (DO-220AA) packages

Search
[75R3245 at newark.com](#)

4.5 V to 18 V Input, 20 A micro-BRICK™ DC/DC Regulator Module



Delivering power density for POL converters, microBRICK SiC931 is the smallest 20 A buck converter module on the market. 4.5 V to 18 V input voltage range & industry-low 1 µA supply current at shutdown

Search
[29AH7320 at newark.com](#)

Go thin to win with Vishay IHLP(R) low-profile inductors



Delivers high performance in low-profile cases. Used for energy storage in DC/DC converters and high current filtering. For designs with minimal headroom

Search
[80R9889 at newark.com](#)

AEC-Q200 qualified CRCW-HP thick film chip resistor



offers engineers up to three times the rated power of standard thick film devices in the same package size, while providing outstanding pulse handling capability

Search
[68R2980 at newark.com](#)

Your Toughest Challenges **Simply Solved** >



As a leading provider of integrated electronic solutions, our business has always been about solving your toughest challenges. By applying a multi-dimensional approach to product design, development and manufacturing, we help bring your vision to life. No matter your industry — from data communications and consumer electronics to industrial, automotive, commercial vehicle and medical — when you work with Molex you know your challenges will simply be solved.

www.molex.com/simplysolved



molex

See Our Expanded Line of Switches

Newark carries a wide range of switches — shop our selection from industry-leading manufacturers like Apem, Honeywell, IDEC, Eaton, Omron, ITW Switch, Schneider Electric, Crouzet Switch, and NKK Switches.

See our entire portfolio at newark.com/switches

Anti Vandal Pushbutton Switches



61T7792

Designed for security and reliability in a variety of panel mount industrial and building applications. Our Anti-Vandal switches are available in panel sizes of 16, 19, 22 and 25 mm, and with various pushbutton symbols including Spot, Ring, and Power Logo. Switches are sealed to IP67 and available in single and double pole configurations.

Rocker Switches



15N9114

Rocker switches are commonly used to directly power a device. They're used in surge protectors, display monitors, computer power supplies, and more. With independent circuitry, they can have a light activated on their face in both the on and/or off positions, which allows the switch to be found easily in the dark.

Limit Switches



17C9878

Limit switches are operated by the motion of a machine part or presence of an object. They are used for controlling machinery as part of a control system, as a safety interlocks, or to count objects passing a point in an assembly line or manufacturing process.

Snap Action Switches



73K2467

An electric switch that is actuated by very little physical force, through the use of a tipping-point mechanism. The Switches are designed for accuracy, repeatability and enhanced product life. They are small size and light weight and combined with ample electrical capacity, precision operation, and extended life.

Joysticks



84R1055

An input device consisting of a stick that pivots on a base and reports its angle or direction to the device it is controlling. The input device is mostly used for gaming applications and sometimes in graphics applications. A joystick also can be helpful as an input device for people with movement disabilities.

Toggle Switches



11M1830

Toggle switches are either lever-type or rocker-type electrical switches with two or three switch positions. A 2-way switch has on-off positions and a 3-way switch has on-off-on positions. Newark also stocks a variety of toggle switch covers and enclosures for protection & security.

Our switch selection is tough to beat!

- Anti Vandal Switches
- DIP Switches & SIP Switches
- Electronic Switches
- Emergency Stop Switches / E Stop
- Joystick Switches
- Key - Keylock Operated Switches
- Keypads
- Limit Switches & Detector Switches
- Microswitch Snap Action Switches
- Navigation Switches
- Pushbutton Switches
- Reed Switches & Magnetic Switches
- Rocker Switches
- Rotary Switches
- Safety Interlock Switches
- Slide Switches
- Switch Accessories & Switch Assortment
- Switch Components
- Switch Development Kits
- Tactile Switches
- Thumbwheel Switches
- Toggle Switches
- Touch Buttons
- Wireless Command

See Our Expanded Line of Relays

We also stock a large variety of relays and related components including those for use in computer, automotive, telecommunication, military and aerospace, medical, instrumentation, industrial, alternative energy and consumer market segments.

See our entire portfolio at newark.com/relays

General Purpose



17M0190

General purpose relays are applied mainly in industrial and power automation systems, in signaling and protection systems, and in other control and electric drive systems. They are also suitable for more common controlling applications like building automation or HVAC systems.

MOSFET Relays



29Y9191

MOSFET relay offers superior performance to an electromechanical relay in many applications. It is a solid-state device that replaces a coil-activated mechanical switch with an optically isolated input stage driving a MOSFET.

Solid State Relays



17M6663

Solid State Relays are semiconductor equivalents of the electromechanical relay and can be used to control electrical loads without the use of moving parts. They may be designed to switch either AC or DC to the load.

Contactors



92F5940

A contactor is an electrically-controlled switch used for switching an electrical power circuit. A contactor is typically controlled by a circuit which has a much lower power level than the switched circuit, such as a 24-volt coil electromagnet controlling a 230-volt motor switch.

Reed Relays



46M4523

A reed relay uses an electromagnet to control one or more reed switches. The contacts are of magnetic material and the electromagnet acts directly on them without requiring an armature to move them. Sealed in a long, narrow glass tube, the contacts are protected from corrosion.

Time Delay Relay



48F5942

Their purpose is to control an event based on time. The difference between relays and time delay relays is when the output contacts open & close: on a control relay, it happens when voltage is applied and removed from the coil; on time delay relays, the contacts can open or close before or after some time delay.

Our relay portfolio is second to none!

- Automotive Relays
- Multi Voltage Relays
- Relay Accessories
- Solid State Relays & Contactors
- Current Monitoring Relays
- Phase Monitoring Relays
- Relay Kits
- Time Delay Relays - Electromechanical
- Ground Fault Monitoring Relays
- Power Relays
- Safety Relays
- Voltage Monitoring Relays
- Mercury Displacement Relays
- Reed Relays
- Signal Relays

Best-Sellers, New Products, Top Suppliers!



Infineon Technologies AG is a world leader in semiconductor solutions with a focus on Energy Efficiency, Mobility, Security and IoT & Big Data.



Renesas Electronics Corporation delivers trusted embedded design innovation with complete semiconductor solutions for a broad range of Automotive, Industrial, Home Electronics, Office Automation and Information Communication Technology applications.



Power Integrations, Inc. is a leading innovator in semiconductor technologies for high-voltage power conversion. The company's products are key building blocks in the clean-power ecosystem.



ON Semiconductor is a leading supplier of semiconductor-based solutions to unique design challenges in automotive, communications, computing, consumer, industrial, medical, aerospace and defense applications.



Offering one of the industry's broadest product portfolios, ST serves customers across the spectrum of electronics applications with innovative semiconductor solutions for Smart Driving and the Internet of Things.



NXP enables secure connections and infrastructure for a smarter world, advancing solutions that make lives easier, better and safer. As the world leader in secure connectivity solutions for embedded applications, NXP is the ideal choice for your newest designs.



Maxim Integrated develops innovative analog and mixed-signal products and technologies to make systems smaller and smarter, with enhanced security and increased energy efficiency.



The future of electronics is wireless and portable due to an almost insatiable consumer demand for ever greater levels of freedom and flexibility. Nordic Semiconductor is playing a key role in the realization of that future.



Silicon Labs is the leader in silicon, software and solutions for a smarter, more connected world. Explore the devices, software and tools that provide comprehensive solutions to develop products that transform industries and improve lives.



Offering a wide range of products including modules, cables, and integrated circuits for USB connectivity, super bridging MCUs and display systems. FTDI Chip strives to bridge multiple technologies and supports this strategy with feature-rich products that include technical documentation, application/software examples, and royalty free drivers.



Leading provider of Semiconductor products servicing thousands of diverse customer applications worldwide. Key products include: microcontrollers, Serial EEPROM devices, Serial SRAM devices, embedded security devices, radio frequency (RF) devices, thermal, power and battery management analog devices, as well as linear, interface and wireless solutions.



Cypress targets markets that are growing faster than the overall semiconductor industry, including innovative segments in the automotive, industrial, home automation and appliances, medical products and consumer electronics businesses.



Global leader providing all-programmable devices suitable for a wide variety of applications and markets ranging from Machine Learning, 5G Wireless, Cloud Computing, Industrial IoT, Aerospace & Defense, Automotive and Consumer Electronics.



Flagship memory solutions optimized for the energy, data and security demands of IoT devices designed for the industrial, consumer, medical and communications markets.



World class industrial storage solutions for the aerospace, military, telecommunications, industrial, medical, gaming and automotive industries, as well as diverse OEM embedded systems applications.

Air movement experts.

Delivering optimal and reliable performance in the harshest conditions.

ebm-papst's IP68 rated fans range in size from 60 mm to 190 mm and are ideal for applications with extreme environmental challenges. Complete encapsulation of the motor blocks any particles of water or dust from penetrating the electronics while also protecting the user from potentially harmful contact. Additional protection classes for other voltages and sizes are available upon request:

sales@us.ebmpapst.com

See more ebm-papst fans at newark.com/ebm-papst

ebmpapst

the engineer's choice





HAMMOND
MANUFACTURING®

HUNDREDS OF INDUSTRIES
THOUSANDS OF MODELS IN STOCK
**UNLIMITED
APPLICATIONS**



www.newark.com/hammond